

Rapid bacterial colony classification using deep learning

Son Ali Akbar^{1,2}, Kawarul Hawari Ghazali², Habsah Hasan³, Zeehaida Mohamed³,
Wahyu Sapto Aji^{1,2}, Anton Yudhana¹

¹Department of Electrical Engineering, Universitas Ahmad Dahlan, Yogyakarta, Indonesia

²Faculty of Electrical and Electronics Engineering Technology, Universiti Malaysia Pahang, Pahang, Malaysia

³School of Medical Sciences, Universiti Sains Malaysia, Kelantan, Malaysia

Article Info

Article history:

Received Sep 11, 2021

Revised Feb 7, 2022

Accepted Feb 18, 2022

Keywords:

Bacterial colonies

Deep learning

Support vector machine

Transfer learning

ABSTRACT

Bacterial colonies infection is one of the causes of bloodstream disease, and it can be a fatality. Therefore, medical diagnoses require fast identification and classification of organisms. Artificial Intelligence with deep learning (DL) can now be developed as a rapid bacterial classification. The research aims to combine deep learning and support vector machines (SVM). The ResNet-101 model of the DL algorithm extracted the image's features using transfer learning then classified by the SVM classifier. According to the experimental results, this model had 99.61% accuracy, 99.58% recall, 99.58% precision, and 99.97% specificity. The technique presented might enhance clinical decision-making.

This is an open access article under the [CC BY-SA](https://creativecommons.org/licenses/by-sa/4.0/) license.



Corresponding Author:

Son Ali Akbar

Department of Electrical Engineering, Universitas Ahmad Dahlan

Yogyakarta, Indonesia

Email: sonali@ee.uad.ac.id

1. INTRODUCTION

Bacterial colonies infection is a prevalent disease that infected human bloodstream and made chiefly mortality in several countries [1]. In past, microbiologist was classified the bacterial species through conventional microscope where needs hard skills and takes more time [2], [3]. However, that approach obviously could be delayed treatment and antimicrobial therapy that can fatality [4]. Therefore, rapid diagnose is significant issues to improve quality of bacterial detection. Current computer-aided diagnosis (CAD) based image processing and machine learning proposed bacterial classification in clinical microbiology accurately. Besides, CAD utilized several machine learning (ML) approach to classify the various bacterial species that used some classifiers such as support vector machine (SVM), backpropagation neural network (BPNN), real AdaBoost, and modest AdaBoost [5]-[13]. However, the CAD process includes traditional methods such as handcrafted features [14]. Recently, deep learning (DL) a subset of machine learning [15]-[17], that have an advantages for medical image analysis[18]-[26]. The beneficial of deep learning is proposed non-handcrafted approach [17]. That utilized numerous convolutional neural network (CNN) layers, it is possible to enhance the classification performance, particularly to improve decision-making. As result, Lopez *et al.* proposed constructing 3x3 convolutional layers for mycobacterium tuberculosis image classification which obtained receiver operating characteristic (ROC) curve of 99% [27]. In addition, high sensitivity score of 83.78% has achieved to classify tuberculosis bacteria images by Kant *et al.* who developed five-layered fully-convoluted neural network architecture combined with a cascading method [28]. Furthermore, Kim *et al.* has proposed an experiment utilizing the CNN model based on the pre-trained DensNet framework, that used to classify bacterial image on optical diffraction tomography (ODT) and is achieved an accuracy of 85% [29]. Therefore, CNN architec-

tures are proven improving the accuracy of classification performances without handcrafted features approach. However, during training the dataset using convolutional layer, that possible generates overfitting and time-consuming [30]-[32]. On the other hand, the experimental conducted by Zielinski *et al.* and Wahid *et al.* who are proposed hybrid DL and ML approach to classify the bacterial species that significant enhance the accuracy rate [33], [34]. The advantages of hybrid method is reduce misclassification and rapid processing. In addition, the success of the classification task, that can be determined by a robust classifier algorithm. Based on the literature, a reliable classifier algorithm is the SVM classifier [8], [34]. Hence, this study proposed to modify the hybrid method for enhancing the accuracy classification performance and prediction score. In addition, all coding generates on graphics processing unit (GPU) it is to optimize the training process [35], [36]. Furthermore, this study is also provided comparing performance between the classical transfer learning approach and the proposed method.

2. MATERIAL AND METHODS

2.1. Dataset preparation

The datasets were collected from the Parasitology Laboratory at Universiti Sains Malaysia. During data collection, the microbiologists provided class labeling of the bacterial species. Figure 1 shows image classes of six bacterial organism samples (*Burkholderia pseudomallei sp.*, *Hemophilus influenzae sp.*, *Klebsiella pneumoniae sp.*, *Pseudomonas aeruginosa sp.*, *Staphylococcus aureus sp.*, and *Streptococcus pneumoniae sp.*). The bacterial samples were provided using the gram stain reaction. The samples are included positive cocci, diplococci, and negative bacilli. A Olympus BX40 light microscope series is used to magnify the bacterial object on Gram-stained slides under 40x magnification. The datasets are provided 44,985 images with the pixel size 244x244 pixels size.




Figure 1. Bacterial organism of (a) *Burkholderia pseudomallei sp.*, (b) *Hemophilus influenzae sp.*, (c) *Klebsiella pneumoniae sp.*, (d) *Pseudomonas aeruginosa sp.*, (e) *Staphylococcus aureus sp.*, and (f) *Streptococcus pneumoniae sp.*

2.2. Data augmentation

Recently, DL techniques are most popular in medical fields, such as biomedical imaging [18]. DL needs an enormous amount of dataset for the learning process. If the resulting data were too narrow or too small, it could add sampling bias towards the bulk of each class [32]. Thus, the DL model with low quantities of data can obtain poor performance results [37]. Rachmadi *et al.* and Mikoajczyk *et al.* are described the data augmentation possible training an efficient model and enhance the learning performance [38], [39]. Therefore, this study was conducted data augmentation to enlarge datasets utilizing transformation image techniques such as, translation, rotation, scaling, flipping, and reflection.

2.3. Transfer learning

Recently, DL perform is provided the transfer learning approach. This is significantly improved computational for training and validation [40]-[42]. In CAD, the advantages are utilized to reducing data labeling, and use existing models [43]. The transfer learning technique is utilized the pre-trained CNN network which involved fine-tuning process on convolution layers. That method applied while freeze the first layer and updating weight on each layer [44]. In the end, the fully-connected and softmax layer is used for classification. This study proposed ResNet-101 pre-trained CNN network, that model lead in ILSVRC 2015 classification task [45].

2.4. Deep feature extraction using CNN

DL was performed in the deep feature extraction by utilizing a pre-trained CNN model. It works by reducing the CNN activation dense dimensionality. Activation layers conduct a deep feature extraction in

a pre-trained network as in [44], [46]. This process resulted in feature vectors from the pre-trained weight model. The forward-backward iteration during the training process identifies the correct weights. Hence, this method can minimize binary cross-entropy (misclassification cost). A pre-trained ResNet-101 model is utilized in this study. The proposed method is provided bacterial image classification that it modified the deep feature extraction technique. Figure 2 shows the architecture model. The method is extracted features from the early convolution layers. It showed on conv1 layer that extracted the shallow features. In these case, the feature is tend to be shallower, more localized, and have a better spatial resolution on earlier layers. Furthermore, the max-pooling layer is added to the lower layer to perform subsampling. Finally, multiple feature maps are normalized using local response normalization, later, the new feature was classified. The classification layer on pre-trained network was discard and change by using SVM classifier.




Figure 2. The proposed method modified CNN deep feature extraction

2.5. Classifier

2.5.1. Softmax classifier

The last step of the generated CNNs model was to extract vectors in fully connected layers. Additionally, the fully connected layers affected the performance of CNN models with a linear feature variable was present by [47]. Thus, those features were necessary to be classified using a softmax classifier as a linear classifier. On the other hand, a softmax classifier could also be used for multi-class classification in binary classification tasks that generalized the logistic regression model. In hinge loss functions describes by [48], a mapping function h is denoted as the dot product of x_i as data input and weight matrix of w , as (1):

$$h(x_i, w) = w \cdot x_i \quad (1)$$

besides, output values were represented as unnormalized log probabilities to class tags, unlike in the hinge loss function. Those output values were changed with the cross-entropy loss function as shown in (2) and the output in (3).

$$E_i = -\log \frac{e^{k y_i}}{\sum_j e^{k_j}} \quad (2)$$

$$k = h(x_i, w) \quad (3)$$

2.5.2. SVM classifier

An effective classifier is the SVM classifier. Goals for separating of multi-class with the selection of a hyperplane significantly increase margin using optimization explained by [27], SVM consists of finding the solution:

$$\begin{aligned} \min_{w, b, \zeta_i} F(\vec{w}, \vec{\zeta}) &= \frac{1}{2} w^T w + C \sum_{n=1}^N \zeta_i \\ \text{st. } y_i [w^T \varphi(x_i) + b] &\geq 1 - \zeta_i \\ \zeta_i &\geq 0, n = 1, \dots, N \end{aligned} \quad (4)$$

where N, x_n is a training vector with labels y_i . Thus, the weight vector, bias, and slack variable are w, b, ζ_i . Meanwhile, $C \geq 0$ is a constant error rate, then φ is the non-linear kernel function. At the same time, SVM intends to minimize the classification error and maximize the margin size by determining an optimal hyperplane. As known, Lagrange multipliers can resolve the optimization issues by modifying the primal space to dual space, as (5):

$$L(a) = \sum_{n=1}^n \alpha_i - \frac{1}{2} \sum_{n=1}^n \sum_{n=1}^n \alpha_i \alpha_i y_i y_j x_i^T x_j \tag{5}$$

which subjects to:

$$\sum_{n=1}^n \alpha_i y_i = 0, 0 \geq \alpha_i \geq c, i = 1, 2, \dots, n \tag{6}$$

in a non-linearity state, $\varphi(x_i)$ as a mapping function can replace x into a high dimensional feature. For the kernel function, SVM can use $k(x_i x_j) = \varphi(x_i x_j)$ to increase the optimization process. Hence, it can be defined as in (7).

$$L(a) = \sum_{n=1}^n \alpha_i = \frac{1}{2} \sum_{n=1}^n \sum_{n=1}^n \alpha_i \alpha_i y_i y_j k(x_i x_j) \tag{7}$$

2.6. Computational hyperparameters

The domain of hyperparameters is considered to train the dataset using pre-trained CNN models. The Adam optimization algorithm as an optimizer is used to optimized for training the models. Instead of the classical stochastic gradient descent procedure, the Adam optimizer possibly creates efficient computational power and utilizes little memory that showed by [49]. The training of the dataset was conducted by using MATLAB software and supported by RTX 2070 Super GPU series with 32 GB memory. Table 1 shows setup the hyperparameters setting in proposed models.

Table 1. Selected hyper-parameters

Parameter	Optimizer	Learning rate	Epoch	Bacth size
VGG16	Adam	0.1^{e-5}	15	32
VGG19	Adam	0.1^{e-5}	15	32
InceptionV3	Adam	0.1^{e-5}	15	32
ResNet-101	Adam	0.1^{e-5}	15	32

2.7. Evaluation performance

There are numerous efforts in deep learning studies, not all researchers report computational cost, but entirely depend on model assessment. Besides, with the confusion matrix explained of [50], that can assess each model's performance. To determine the percentage of each organism that was correctly classified with statistical parameters, such as recall (positive sample correctly classified), specificity (negative sample correctly classified), and precision (positive class were actually positive). The metric evaluation as follows:

$$recall = \frac{TP}{TP + FN} \tag{8}$$

$$specificity = \frac{TN}{TN + FN} \tag{9}$$

$$precision = \frac{TP}{TP + FP} \tag{10}$$

in (8)-(10) explained the number of predictions in which the classifier correctly predicts. TP is defined the number of cycles correctly classified as true bacterial, and TN denotes the number of cycles correctly classified as false bacterial. FP denotes the number of cycles wrongly correctly classified as false bacterial, and FN denotes the number of cycles wrongly correctly classified as true bacterial.

3. RESULT AND DISCUSSION

Recent years, Lamy *et al.* explained the golden standard used blood culture gram-stained classification based on the shape and color using a microscope [51]. However, those producing are incorrect gram stain interpretation from the reader error of 9% to 45% using standardized criteria evaluation [3]. Besides, due to the limitation influencing delayed diagnosis and treatment, thus that needs an other approaches to handle the problem for expert use. This study develops an AI-based algorithm using deep learning CNN-based for rapid bacterial specimen identification. The proposed method is consist to enhance the classification performance and reduce time-consuming of diagnosis. In the experiment, the recommended pre-trained models such VGGNet (VGG16, VGG19) [33] and InceptionV3 [52] are tested to compare the result between the proposed method using ResNet-101 model. On the other hand, the datasets were divided 70% and 30% for data training and data testing. The first approach, the transfer learning method is used training and testing the datasets. During training, overfitting can be decreased accuracy performance [53]. Hence, the cross-entropy loss function was used to minimize loss and optimizing the classification model [48], [50]. The result of the first approach illustrates in Figures 3-7, which is shown the training period of accuracy and loss graphs from four pre-trained CNN models VGG16, VGG19, InceptionV3, ResNet101. The proposed method in second approach, this study utilized convolution layers to conduct modified deep extraction feature technique, which is the extracted features from the early convolution layers will proceed on SVM classifier. Furthermore, Table 2 shows the accuracy achievement comparison that obtained from three pre-trained CNN model. The high accuracy performance was achieved the proposed method of 99.61% by using ResNet-101 model, which modified deep feature extraction technique. In addition, the best processing time in the first approach is 79.20 m/s, but the proposed method is faster than the first approach, which is 9.19 m/s (see Table 3).




Figure 3. The training and validation graph of accuracy and loss per epoch on VGG16




Figure 4. The training and validation graph of accuracy and loss per epoch on VGG19 model




Figure 5. The training and validation graph of accuracy and loss per epoch on InceptionV3 model




Figure 6. The training and validation graph of accuracy and loss per epoch on Resnet-101 model




Figure 7. The training and validation curve of accuracy and loss per epoch of each model curve line description

Other evaluated performance parameters were recall, precision, and specificity scores. Table 4 shows the comparison of both method performances. As shown in Table 4, the first proposed method accomplished 99.30% recall, 99.37% precision, and 99.88% specificity. Improved performance was shown in the implementation result of the second proposed method, which increased up to 28% of recall, 26% of precision, and 9% of specificity more than the performance results of the first proposed method. The second proposed method could

reduce the number of false-negative detections in clinical diagnosis to reduce excessive anxiety in the patient being treated. To performance comparison, the accuracy assessment in image classification was used to evaluate the proposed training validation set and the CNN model. The proposed models were compared with other models which utilized gram-stained images. We evaluated the CNN model with various layers configuration. The performance results did not show any significant divergence between models which were previously tested in this study. For instance, this stage are tested the dataset using the method proposed [34], which resulted in only a slight difference in the accuracy performance, which was 0.74%. Nevertheless, different datasets and hyperparameters settings might influence the divergent performance results. Table 5 shows the comparison of proposed model with other methods. the proposed methods performed superiority over other models. Hence, it could serve as an aided tool for bacterial classification based on Gram-stained images.

Table 2. The accuracy of classification

CNN Models	Transfer learning (Acc %)	Deep feature + SVM (Acc %)
ResNet-101	99.34	99.61
InceptionV3	98.98	99.44
VGG19	98.14	98.99
VGG16	97.78	99.05

Table 3. Processing time

CNN Models	Transfer learning (m/s)	Deep feature + SVM (m/s)
ResNet-101	118.28	9.19
InceptionV3	177.00	14.39
VGG19	147.00	48.20
VGG16	79.20	47.24

Table 4. The comparison classification result between CNNs model

2-7 CNN Models	Transfer learning (%)			Deep feature + SVM (%)		
	Recall	Precision	Specificity	Recall	Precision	Specificity
ResNet-101	99.30	99.37	99.88	99.58	99.58	99.97
InceptionV3	98.90	99.00	99.83	99.42	99.15	99.91
VGG19	98.22	98.35	99.70	98.87	98.88	99.85
VGG16	97.62	97.82	99.63	99.02	99.03	99.84

Table 5. The comparison of accuracies performance between the proposed method and other methods

Author	Methods	Accuracy (%)
H. Sajedi, <i>et al.</i> [54]	Gabor Feature, XGboost classifier	90.28
K.P. Smith, <i>et al.</i> [52]	InceptionV3	94.90
B. Zieliński, <i>et al.</i> [33]	VGG, SVM classifier	97.24
F. Wahid, <i>et al.</i> [34]	InceptionV3, SVM classifier	98.70
Proposed method 1	ResNet-101, softmax classifier	99.34
Proposed method 2	ResNet-101, SVM Classifier	99.61

4. CONCLUSION

In this study, rapid classification based deep learning method has been proposed to improve the prediction result and fast recognition of bacterial colony species. The datasets are provided of six bacterial species that caused patient acute infection symptoms. The proposed method is modified deep feature extraction technique using the pre-trained CNN layers, which is extracted features on shallow convolution. Then the classification process conducted using SVM classifier. The proposed method utilized the ResNet-101 CNN architecture for trained and tested the datasets and compared with three CNN models. As results, the classification performance obtained high accuracy of 99.61% rather than use the transfer learning approach. The prediction score involved three matrix parameter measurement that achieved 99.58% recall, 99.58% precision, and 99.97% specificity. Besides, the classification time touched fastest time processing of 9.19 m/s. Hence, this study has been proven to be successful in enhancing classification accuracy and less time consuming. Furthermore, the bacterial colony detector's success in rapid bacterial species classification set this study apart from other

transfer learning studies. In future works, the architecture will be applied for real-time various microorganism species detection.

ACKNOWLEDGEMENT




The author would like to thank Universiti Sains Malaysia and Universitas Ahmad Dahlan for extending all the necessary facilities for successful completion of this work.

REFERENCES




- [1] K. Laupland, "Incidence of bloodstream infection: a review of population-based studies," *Clinical Microbiology and Infection*, vol. 19, no. 6, pp. 492–500, Jun. 2013, doi: 10.1111/1469-0691.12144.
- [2] J. Barenfanger *et al.*, "Decreased mortality associated with prompt gram staining of blood cultures," *American Journal of Clinical Pathology*, vol. 130, no. 6, pp. 870–876, Dec. 2008. doi: 10.1309/AJCPVMDQU2ZJDPBL.
- [3] L. P. Samuel, J.-M. Balada-Llasat, A. Harrington, and R. Cavagnolo, "Multicenter assessment of gram stain error rates," *Journal of Clinical Microbiology*, vol. 54, no. 6, pp. 1442–1447, Jun. 2016, doi: 10.1128/JCM.03066-15.
- [4] M. J. Schwaber and Y. Carmeli, "Mortality and delay in effective therapy associated with extended-spectrum-lactamase production in enterobacteriaceae bacteraemia: a systematic review and meta-analysis," *Journal of Antimicrobial Chemotherapy*, vol. 60, no. 5, pp. 913–920, 2007, doi: 10.1093/jac/dkm318.
- [5] P. P. Bourbeau and N. A. Ledebouer, "Automation in clinical microbiology," *Journal of Clinical Microbiology*, vol. 51, no. 6, pp. 1658–1665, Jun. 2013, doi: 10.1128/JCM.00301-13.
- [6] K. Smith and J. Kirby, "Image analysis and artificial intelligence in infectious disease diagnostics," *Clinical Microbiology and Infection*, vol. 26, no. 10, pp. 1318–1323, Oct. 2020, doi: 10.1016/j.cmi.2020.03.012.
- [7] P. J. Chiang, M. J. Tseng, Z. S. He, and C. H. Li, "Automated counting of bacterial colonies by image analysis," *Journal of Microbiological Methods*, vol. 108, pp. 74–82, 2015, doi: 10.1016/j.mimet.2014.11.009.
- [8] Y. Song, L. He, F. Zhou, S. Chen, D. Ni, B. Lei, and T. Wang, "Segmentation, splitting, and classification of overlapping bacteria in microscope images for automatic bacterial vaginosis diagnosis," *IEEE Journal of Biomedical and Health Informatics*, vol. 21, no. 4, pp. 1095–1104, Jul. 2017, doi: 10.1109/JBHI.2016.2594239.
- [9] M. Shah, S. Mishra, M. Sarkar, and C. Rout, "Automatic detection and classification of tuberculosis bacilli from ZN-stained sputum smear images using watershed segmentation," In *International Conference on Signal Processing (ICSP 2016)*, 2016, doi: 10.1049/cp.2016.1459.
- [10] V. Vapnik, "An overview of statistical learning theory," *IEEE Transactions on Neural Networks*, vol. 10, 1999, doi: 10.1109/72.788640.
- [11] D. E. Rumelhart, G. E. Hinton, and R. J. Williams, "Learning representations by back-propagating errors," *Nature*, vol. 323, pp. 533–536, 1986.
- [12] R. E. Schapire and Y. Singer, "Improved boosting algorithms using confidence-rated predictions," *Machine Learning volume*, vol. 37, pp. 297–336, 1999, doi: 10.1023/A:1007614523901.
- [13] S. Wu and H. Nagahashi, "A new method for solving overfitting problem of gentle AdaBoost," In *Fifth International Conference on Graphic and Image Processing (ICGIP 2013)*, Dec. 2013, vol. 9069, pp. 329–334, doi=10.1117/12.2050093.
- [14] N. Goel, A. Yadav, and B. M. Singh, "Medical image processing: A review," In *2016 Second International Innovative Applications of Computational Intelligence on Power, Energy and Controls with their Impact on Humanity (CIPECH)*, Nov. 2016, pp. 57–62, doi: 10.1109/CIPECH.2016.7918737.
- [15] Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," *Nature*, vol. 521, no. 7553, pp. 436–444, May 2015.
- [16] Y. Guo, Y. Liu, A. Oerlemans, S. Lao, S. Wu, and M. S. Lew, "Deep learning for visual understanding: A review," *Neurocomputing*, vol. 187, pp. 27–48, Apr. 2016, doi: 10.1016/j.neucom.2015.09.116.
- [17] A. Shrestha and A. Mahmood, "Review of deep learning algorithms and architectures," *IEEE Access*, vol. 7, pp. 53040–53065, 2019, doi: 10.1109/ACCESS.2019.2912200.
- [18] G. Litjens *et al.*, "A survey on deep learning in medical image analysis," *Medical Image Analysis*, vol. 42, 2017, doi: 10.1016/j.media.2017.07.005.
- [19] J. Ker, L. Wang, J. Rao, and T. Lim, "Deep learning applications in medical image analysis," *IEEE Access*, vol. 6, pp. 9375–9389, 2018, doi: 10.1109/ACCESS.2017.2788044.
- [20] L. Cai, J. Gao, and D. Zhao, "A review of the application of deep learning in medical image classification and segmentation," *Annals of Translational Medicine*, vol. 8, no. 11, pp. 713–713, Jun. 2020, doi: 10.21037/atm.2020.02.44.
- [21] A. Esteva *et al.*, "Deep learning-enabled medical computer vision," *NPJ Digital Medicine*, vol. 4, no. 1, Dec. 2021, doi: 10.1038/s41746-020-00376-2.
- [22] M. Kim, J. Yun, Y. Cho, K. Shin, R. Jang, H.-j. Bae, and N. Kim, "Deep learning in medical imaging," *Neurospine*, vol. 16, no. 4, pp. 657–668, Dec. 2019, doi: 10.14245/ns.1938396.198.
- [23] P. R. Jeyaraj and E. R. Samuel Nadar, "Computer-assisted medical image classification for early diagnosis of oral cancer employing deep learning algorithm," *Journal of Cancer Research and Clinical Oncology*, vol. 145, no. 4, pp. 829–837, Apr. 2019, doi: 10.1007/s00432-018-02834-7.
- [24] W. Zhu, L. Xie, J. Han, and X. Guo, "The application of deep learning in cancer prognosis prediction," *Cancers*, vol. 12, no. 3, Mar. 2020, doi: 10.3390/cancers12030603.
- [25] K. Vidhya and R. Shanmugalakshmi, "Deep learning based big medical data analytic model for diabetes complication prediction," *Journal of Ambient Intelligence and Humanized Computing*, vol. 11, no. 6, 2020, doi: 10.1007/s12652-020-01930-2.
- [26] H. J. Jang and K. O. Cho, "Applications of deep learning for the analysis of medical data," *Archives of Pharmacal Research*, vol. 42, no. 6, pp. 492–504, 2019, doi: 10.1007/s12272-019-01162-9.

- [27] Y. P. Lopez, C. Costa Filho, L. Aguilera, and M. Costa, "Automatic classification of light field smear microscopy patches using convolutional neural networks for identifying mycobacterium tuberculosis," In *2017 CHILEAN Conference on Electrical, Electronics Engineering, Information and Communication Technologies (CHILECON)*, Oct. 2017, pp. 1–5, doi: 10.1109/CHILECON.2017.8229512.
- [28] S. Kant and M. M. Srivastava, "Towards automated tuberculosis detection using deep learning," In *2018 IEEE Symposium Series on Computational Intelligence (SSCI)*, Nov. 2018, pp. 1250–1253, doi: 10.1109/SSCI.2018.8628800.
- [29] G. Kim, Y. Jo, H. Cho, G. Choi, B. S. Kim, H. S. Min, and Y. Park, "Automated identification of bacteria using three-dimensional holographic imaging and convolutional neural network," In *2018 IEEE Photonics Conference (IPC)*, Sep. 2018, pp. 1–2, doi: 10.1109/IPCon.2018.8527133.
- [30] A. Ferrari, S. Lombardi, and A. Signoroni, "Bacterial colony counting with convolutional neural networks in digital microbiology imaging," *Pattern Recognition*, vol. 61, pp. 629–640, 2017, doi: 10.1016/j.patcog.2016.07.016.
- [31] C.-p. Kuok, M.-h. Horng, Y.-m. Liao, N.-h. Chow, and Y.-n. Sun, "An effective and accurate identification system of Mycobacterium tuberculosis using convolution neural networks," *Microscopy Research and Technique*, vol. 82, no. 6, pp. 709–719, Jun. 2019, doi: 10.1002/jemt.23217.
- [32] J. M. Johnson and T. M. Khoshgoftaar, "Survey on deep learning with class imbalance," *Journal of Big Data*, vol. 6, no. 1, Dec. 2019, doi: 10.1186/s40537-019-0192-5.
- [33] B. Zieliński, A. Plichta, K. Misztal, P. Spurek, M. Brzywczy-Włoch, and D. Ochońska, "Deep learning approach to bacterial colony classification," *PLOS ONE*, vol. 12, no. 9, Sep. 2017, doi: 10.1371/journal.pone.0184554.
- [34] M. F. Wahid, M. J. Hasan, M. S. Alom, and S. Mahub, "Performance analysis of machine learning techniques for microscopic bacteria image classification," In *2019 10th International Conference on Computing, Communication and Networking Technologies (ICCCNT)*, Jul. 2019, pp. 1–4, doi: 10.1109/ICCCNT45670.2019.8944597.
- [35] Z. Chen, J. Wang, H. He, and X. Huang, "A fast deep learning system using GPU," In *2014 IEEE International Symposium on Circuits and Systems (ISCAS)*, 2014, no. 1, pp. 1552–1555, doi: 10.1109/ISCAS.2014.6865444.
- [36] S. Shi, Q. Wang, P. Xu, and X. Chu, "Benchmarking state-of-the-art deep learning software tools," In *2016 7th International Conference on Cloud Computing and Big Data (CCBD)*, Aug. 2016, pp. 99–104, doi: 10.1109/CCBD.2016.029.
- [37] A. Krizhevsky and G. Hinton, "Convolutional deep belief networks on cifar-10," vol. 40, no. 7, pp. 1–9, 2010.
- [38] R. F. Rachmadi, I. K. Eddy Purnama, M. H. Purnomo, and M. Hariadi, "A systematic evaluation of shallow convolutional neural network on CIFAR dataset," *IAENG International Journal of Computer Science*, vol. 46, no. 2, pp. 365–376, 2019.
- [39] A. Mikolajczyk and M. Grochowski, "Data augmentation for improving deep learning in image classification problem," In *2018 International Interdisciplinary PhD Workshop (IIPHDW)*, May 2018, pp. 117–122, doi: 10.1109/IIPHDW.2018.8388338.
- [40] W. Zhang, R. Li, T. Zeng, Q. Sun, S. Kumar, J. Ye, and S. Ji, "Deep model based transfer and multi-task learning for biological image analysis," *IEEE Transactions on Big Data*, vol. 6, no. 2, pp. 322–333, Jun. 2020, doi: 10.1109/TBDATA.2016.2573280.
- [41] K. Weiss, T. M. Khoshgoftaar, and D. Wang, "A survey of transfer learning," *Journal of Big Data*, vol. 3, no. 1, Dec. 2016, doi: 10.1186/s40537-016-0043-6.
- [42] M. Hussain, J. J. Bird, and D. R. Faria, "A study on CNN transfer learning for image classification," In *UK Workshop on Computational Intelligence*, 2019, vol. 840, pp. 191–202, doi: 10.1007/978-3-319-97982-3_16.
- [43] H.-C. Shin *et al.*, "Deep convolutional neural networks for computer-aided detection: CNN architectures, dataset characteristics and transfer learning," *IEEE Transactions on Medical Imaging*, vol. 35, no. 5, pp. 1285–1298, May 2016, doi: 10.1109/TMI.2016.2528162.
- [44] A. Brock, T. Lim, J. M. Ritchie, and N. Weston, "FreezeOut: accelerate training by progressively freezing layers," 2017, *arxiv: 1706.04983*.
- [45] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, Jun. 2016, pp. 770–778, doi: 10.1109/CVPR.2016.90.
- [46] M. Jogin, Mohana, M. S. Madhulika, G. D. Divya, R. K. Meghana, and S. Apoorva, "Feature extraction using convolution neural networks (CNN) and deep learning," In *2018 3rd IEEE International Conference on Recent Trends in Electronics, Information and Communication Technology (RTEICT)*, May 2018, pp. 2319–2323, doi: 10.1109/RTEICT42901.2018.9012507.
- [47] S. S. Basha, S. R. Dubey, V. Pulabaigari, and S. Mukherjee, "Impact of fully connected layers on performance of convolutional neural networks for image classification," *Neurocomputing*, vol. 378, pp. 112–119, Feb. 2020, doi: 10.1016/j.neucom.2019.10.008.
- [48] F. Zang and J.-s. Zhang, "Softmax discriminant classifier," In *2011 Third International Conference on Multimedia Information Networking and Security*, Nov. 2011, pp. 16–19, doi: 10.1109/MINES.2011.123.
- [49] D. P. Kingma and J. Ba, "Adam: a method for stochastic optimization," 2014, *arxiv: 1412.6980*.
- [50] H. M and S. M.N, "A review on evaluation metrics for data classification evaluations," *International Journal of Data Mining and Knowledge Management Process*, vol. 5, no. 2, pp. 1–11, Mar. 2015, doi: 10.5121/ijdkp.2015.5201.
- [51] B. Lamy, M. Sundqvist, and E. A. Idelevich, "Bloodstream infections – standard and progress in pathogen diagnostics," *Clinical Microbiology and Infection*, vol. 26, no. 2, pp. 142–150, 2020, doi: 10.1016/j.cmi.2019.11.017.
- [52] K. P. Smith, A. D. Kang, and J. E. Kirby, "Automated interpretation of blood culture gram stains by use of a deep convolutional neural network," *Journal of Clinical Microbiology*, vol. 56, no. 3, pp. 1–12, Mar. 2018, doi: 10.1128/JCM.01521-17.
- [53] D. M. Hawkins, "The problem of overfitting," *Journal of Chemical Information and Computer Sciences*, vol. 44, no. 1, pp. 1–12, Jan. 2004, doi: 10.1021/ci0342472.
- [54] H. Sajedi, F. Mohammadipanah, and A. Pashaee, "Image-processing based taxonomy analysis of bacterial macromorphology using machine-learning models," *Multimedia Tools and Applications*, vol. 79, no. 43, pp. 32711–32730, Nov. 2020, doi: 10.1007/s11042-020-09284-9.




BIOGRAPHIES OF AUTHORS

Son Ali Akbar    is now pursuing a doctoral degree in the faculty of electrical and electronics engineering technology, Universiti Malaysia Pahang, Malaysia. He obtained bachelor degree in electrical engineering from Universitas Ahmad Dahlan, Indonesia and master degree in electrical engineering from Universitas Gadjah Mada, Indonesia. His current research interests include biomedical image processing, machine learning and deep learning. He can be contacted at email: sonali@ee.uad.ac.id.






Kamarul Hawari Gazhali    is a professor in the faculty of electrical and electronics engineering technology, Universiti Malaysia Pahang, Malaysia. His current research and publication interests include image processing, machine learning, and deep learning. He can be contacted at email: kamarul@ump.edu.my.






Habsah Hasan    is a professor in the school of medical sciences, Universiti Sains Malaysia, Malaysia. His current research and publication interests include infection control, clinical microbiology, and infectious diseases. She can be contacted at email: drhabsah@usm.my.






Zeehaida Mohamed    is a Professor in the School of Medical Sciences, Universiti Sains Malaysia, Malaysia. His current research and publication interests include Medical Parasitology, Clinical Microbiology. She can be contacted at email: zeehaida@usm.my.



Wahyu Sapto Aji    is a Ph. D. student in the faculty of electrical and electronics engineering technology, University of Malaysia Pahang, Malaysia. Wahyu Sapto Aji obtained a bachelor's and master's degree in electrical engineering from the electrical engineering department of Gadjah Mada University, Yogyakarta, Indonesia. He has been working as a lecturer in the electrical engineering department at Ahmad Dahlan University since 2014. His current research interests include Image Processing, Deep Learning. He can be contacted at email: wahyusa@ee.uad.ac.id.



Anton Yudhana    is a associate professor in the department of electrical engineering, Universitas Ahmad Dahlan, Indonesia. His current research and publication interests include signal and image processing, biomedical engineering, machine learning and deep learning. He can be contacted at email: eyudhana@ee.uad.ac.id.