Electromagnetism-like mechanism algorithm for hybrid flowshop scheduling problems

Smail Khaled, Djebbar Bachir

Department of Computer Science, University Mohamed Boudiaf, Oran, Algeria

ABSTRACT

Article Info

Article history:

Received Apr 18, 2022 Revised Aug 30, 2023 Accepted Sep 24, 2023

Keywords:

Electromagnetism-like mechanism Hybrid flow shop Makespan Metaheurestics Optimization Given the interest and complexity, of the hybrid flow shops (HFS) problem in industry, he has been extensively considered, the HFS, is a complex combinatorial problem supported in many original world applications. We consider a hybrid flow shop FH4(P3, P2)|| C_{max} to applied in this paper. In this papers we attempt to optimize the makespan which refers to the last task completion time by an adequate meta-heuristic algorithm based on electromagnetism mechanism (EM). We also present analysis on the performance of the EM-algorithm adapted to HFS scheduling problems. The electromagnetism-like mechanism method gave us efficient and fair results comparing to particle swarm and genetic algorithm.

This is an open access article under the <u>CC BY-SA</u> license.



Corresponding Author:

Smail Khaled

Department of Computer Science, University Mohamed Boudiaf USTO-MB, BP 1505 Oran M'Naouar, 31000 Oran, Algeria Email: khaled.smail@univ-usto.dz

1. INTRODUCTION

Lee and Vairaktarakis [1] define a hybrid flow shops (HFS) model as a multi-stage flowshop with parallel machines at each stage. He is a general case of the simple FS problem, as shown by Gourgand *et al.* [2]. We study the scheduling of a batch of identical jobs in an homogeneous parallel machines at each stage, to minimize makespan C_{max} , ie. (completion time of the last job in the batch). Resolution of HFS problem through the use of metaheuristic techniques represents a common practice in literature, according to [3]–[10]. Recently, a complete review on research carried out in the field of HFS problem has been presented by Mirabi [11], and Ruiz and Vázquez-Rodríguez [12].

In this article, we use the electromagnetism mechanism (EM) algorithm to arrangement with the HFS problem presented by Figure 1. In section 2, we propose the problem statement and the proposed EM algorithm. The empirical results and their interpretation are described in section 3. Finally, section 4 summarizes our article and indicates future research.

2. PROBLEM STATEMENTS AND ELECTROMAGNETISM-LIKE ALGORITHM

2.1. HFS problem

Xu and Wang [13] assume that the HFS problem as folowing: for all machines the release time is negligible; one job is treated on only one machine at a time; and one machine can process only one transaction. The buffers between stages are unlimited in FHS problem and all n jobs are convenient to be refined at the initial time and are independent. For all of the n jobs, in each machine the treatement times are known and

determined in first time and once an transaction is commenced, it cannot be stoped; the transport time is negligible between the different machines.

ISSN: 2502-4752

The formulated of HFS problem is:

$$\min C_{max} \tag{1}$$

s.t.

$$C_{max} = \max(C_{ik}), \qquad k = 1, ..., s; \quad i = 1, ..., n$$
 (2)

$$C_{ik} = S_{ik} + P_{ik} \tag{3}$$

$$\sum_{i=1}^{m(k)} X_{jik} = 1,$$
(4)

$$S_{ik} \ge C_{i,k-1} \qquad \qquad k = 2, \dots, s \tag{5}$$

$$S_{ik} \ge C_{jk} - M Y_{ijk}, \qquad \forall (i,j)$$
(6)

$$S_{jk} \ge C_{ik} - (1 - M)Y_{ijk} , \quad \forall (i, j)$$

$$\tag{7}$$

$$S_{i1} \ge \mathbf{R}_i \qquad \forall \ i = 1, \dots, n) \tag{8}$$

where C_{ik} represent the completion time of job i; m(k) is the number of the machines at stage k, s is the total number of stages, n is the total number of jobs, $X_{ijk} = 1$ if at stage k, job j is defined to machine i; in another way, $X_{ijk}=0$, $Y_{ijk}=1$ if at stage k, job i predate job j; in another way, $Y_{ijk}=0$, S_{ik} represent the starting time of job i at stage k, Ri represent the release time of job i, P_{ik} represent the process time of job i at stage k, M is a tall constant.

The formulations that are mentioned before described as: (1) designate the objective function to minimize C_{max} , (2) denotes the maximum realization time of all jobs; (3) represent the computation of C_{ik} ; (4) garantee that at every stage, one job is treated explicitly on one machine; (5) and (6) confirm that only one job can process on one machine at one time; (7) indicate that one job cannot be treated until its prior job is accomplished ; (8) determine the starting time of a job. In Figure 1, we illustrate the HFS problem, for scheduling problems and its development in [14], [15], and adopting the recognised three-field notation $\alpha |\beta|\gamma$, the problem considered here can be viewed as FH4(P3,P2)|| C_{max} . i.e 2 stages with three machines in the first stage and two machines in the second stages, and a stock at the access of the first stage and between the stages. Gourgand *et al.* [5] defineted that the total number of feasible solutions is $n! (\prod_{i=1}^{m} m_i)^n$. The flexible flowshop problem (FFS) with only two stages with a single machine is non-deterministic polynomial-time hardness (NP-hard) [16], so the FHS is also NP-hard since it is a general case of the FFS.



Figure 1. Example of HFS problem (FH4 (P3, P2)||C_{max})

2.2. Electromagnetism-like algorithm

Birbil *et al.* [17], [18] present an adequate meta-heuristic algorithm based on EM for unconstrained global optimization of non-linear functions. The charge is related with each solution to the objective function value in a multi-dimensional space. A set of solutions points (population), is create, in whatever solution point will apply repulsion or attraction on more points, the weightness of which is inversely proportional to the square of the distance and proportional to the product of the charges between the solutions points (Coulomb's Law).

Electromagnetism-like mechanism algorithm for hybrid flow-shop scheduling problems (Smail Khaled)

The foundation of the EM-algorithm is that the repulsive solutions will forbid a move in their direction by repelling more points in the population and that attractive point's will facilate moves in their direction. It is a set up of LS in solution space. The fundamental dissimilarity with exist methods is that the moves are controlled by forces that conformed the method of electromagnetism [4].

Recently, EM has been applied to deal with combinatorial optimization problems, let us quote the following cases: Debels *et al.* [4] for an hybrid scatter search/electromagnetism for project scheduling problem, and has also been used by Chang *et al.* [19] to single machine scheduling problem, and by Maenhout and Vanhoucke [20] for the nurse scheduling problem. EM method is converged rapidly with the generated sound solutions [21]–[23]. Other approaches have been based on EM-algorithm, such as [22], [24]–[31]. The processus of EM-Algorithm on the optimization have the following form:

min f(x), subject to $x \in S$

where f(x) is a nonlinear function,

$$S = \{x \in \mathbb{R}^n | -\infty < l_m \le x_m \le u_m < \infty, m = 1, ..., n\}$$

is a bordred appropriate zones of problem. n denote the size of the situation, u_m , l_m are successively the upper and lower bounds of the mth size.

EM is a simulation based on Coulomb's law that describes the repulsion-attraction tool of electromagnetism approach. In Algorithm 1 EM, the solution is represented by a charged particle such that the best solution aspect of the particle represents the highest charge.

The fixed charge of solution *i* is calculated by:

$$q^{i} = \exp\left(-n\frac{f(x^{i}) - f(x^{best})}{\sum_{k=1}^{m} (f(x^{k}) - f(x^{best}))}\right)$$
(9)

where, m is the population size, $f(x^{best})$, $f(x^k)$ and $f(x^i)$ represent respectively, the first-rate solution and the fair values of points k and i.

The amplitude of the effect of repulsion and attraction in the set of solutions is represented by the quality of the solution of each particle. The unacceptable solution dismay more particles to change against other region, while the more excellent solution reassure them to meet to interesting valleys. The total force F^i given by (11) represents the resultant of the force of the solution i compared to the solution j; F^i make use of each solution, indicates the order of the displacement of the particles towards other diversified solutions.

$$F_{j}^{i} = \begin{cases} (x^{j} - x^{i}) \frac{q^{i}q^{j}}{||x^{j} - x^{i}||^{2}} & \text{if } f(x^{j}) < f(x^{i}) & \text{Attractive} \\ (x^{i} - x^{j}) \frac{q^{i}q^{j}}{||x^{j} - x^{i}||^{2}} & \text{else } f(x^{j}) \ge f(x^{i}) & \text{Repulsion} \end{cases}, \forall i \end{cases}$$
(10)

$$F^i = \sum_{j=1, j \neq i}^p F^i_j \tag{11}$$

 F^i decide the direction of evolution for the equivalent point at the successive iterations.

```
Algorithm 1. EM (M_IT, LS_IT, i, \alpha)

M_IT: max iterations

LS_IT: max iterations of L.S.

\alpha \in [0, 1]:L.S. parameter,

Initialize

While (has not met stop criterion) do

L.S. (Local Search)

C.T.F. F() (Calculate Total force)

Move the point by F()

Evaluate the New points

End while
```

Eug wurte

As shown in the fundamental EM algorithm 1, it consists of five steps described as follows:

a) Initialization: initialization procedure is applied to choose randomly k points, pretented to be evenly scattered between the corresponding upper bound u_m and lower bound l_m from the feasible domain of the conjoint variables can be determined as follows:

ISSN: 2502-4752

$$x_m^l = l_m + \alpha . (u_m - l_m)$$
, for m = 1, ..., n, where $\alpha \in U(0, 1)$.

The initialization ends with the choice of the best point x^{best} which has the best function value in the midlle of the k identified points, where $x^{best} = \arg \min_i f(x^i)$.

- b) Local search (L.S.): L.S. procedure is applied only to the best point x^{best} in order to research the region of this solution in the population. It's a random line search algorithm [24]. Firstly, to ensure that the L.S. only achieve suitable points, the procedure L.S. calculates the highest suitable step length $\alpha(\max_m(u_m-l_m))$, secondly it uses a provisional solution y to assign it the best solution x^{best} this for each coordinate m. Then point y is moved forward that direction and a arbitrary number is preffered as the step length. If an improvement is observed, with in the LS_IT iterations, the perfect solution is updated by y and the search forward this dimention m ends. Finally, some points are updated. The reader is referred to [13], [14], [25] for details.
- c) Calculation of charge: for each iteration, the charge of each point changes as it is coincident to their objective function values, thus points that have better objective values have higher charges. The charge q_i of each point i is evaluated by (9), it determines the power of attraction or repulsion of point i.
- d) Calculation of total force vector C.T.F.: the T.F. F^i expend on point *i* is evaluated by the (11). In (10) shows that the solution which has a superior objective function rate acts as an absolute attracting point and invite all more solutions in the population to a improved region. On the contrary, the point with the worst rate of the objective function repels the others.
- e) Move correspondent to the T.F.: using a arbitrary step of length α consistently distributed bounded by 0 and 1, and a vector RNG whose components designate the allowable appropriate move towards the upper destined or the lower destined of the joint variables, in (12) evaluates the new coordinate x^i of the displacement of point i in the order of the T.F. F^i

$$x^{i} = x^{i} + \alpha \frac{F^{i}}{\|F^{i}\|} (RNG) \quad i = 1, 2, ..., k$$
 (12)

The calculation of one iteration of the EM algorithm is completed when the execution of the above five procedures is finished, thus the positions of the points are updated.

3. SIMULATION RESULTS AND ANALYSIS

The EM was tested on HFS containing 2 stages, with 3 machines and a stock on the entry of the first stage and 2 machines in the second stage, and stock among the first stage and the second stage. The number of jobs varies between five and twenty. Figure 1 represents the simplified model of the FSH using Vignier's notation [15], ie FH4(P3,P2)|| C_{max} . Simulations under MATLAB of the EM algorithm was performed on the Intel® coreTM 2 Duo 3.06 GHz computer. Table 1 presents a comparison between our final results - presented in bold - in terms of average C_{max} and the results recently published in the literature [3]. The Averge CPUs for EM in (FH4, C_{max}) of N jobs as presented in Table 2.

Table 1. Average C_{max} for (FH4, C_{max})									
N jobs	Iterations								
	100 500 1000						1000		
	GA	PSO	ME	GA	PSO	ME	GA	PSO	ME
5	130	148	131	205	135	122	190	186	154
10	214	271	206	118	273	140	125	249	121
15	302	367	298	291	404	229	309	431	274
20	421	556	391	397	521	337	383	529	359
	Average C _{max}								

Table 2. Average CPU _s for EM	(in (FH4, C _{max}))
--	-------------------------------

jobs	Average CPUs(sec)
5	0.56
10	1.21
15	4.15
20	7.18

Ν

Electromagnetism-like mechanism algorithm for hybrid flow-shop scheduling problems (Smail Khaled)

In general, we compare the results given by the application of (EM) to the FSH studied with other approaches in the literature; we note that these results are competitive. Figures 2 and 3 (value of cost average C_{max}) shows the comparison between the EM, PSO and GA for 5, 10, 15, and 20 jobs at different number of iterations (100, 500, and 1,000).

In Figure 2, the coordinate x represents the number of jobs as the coordinate y represents the average C_{max} . In order to show that the EM is qualified to produce fairness results given the additional processing time, we increased the number of iterations up to 1,000 iterations. The average C_{max} is speedily diminished at the starting point of the search where the N_Jobs=10 for a N_Iter=500 and N_Iter=1,000 Figure 2, hence the expectation of having more acceptable solutions in these experiments overdue to the competence of the EM to research various regions of the solution domain. The Figure 3 as well shows that by extending N_Iter=1,000, EM is qualified to find a good values compared to PSO and GA. According to the comparison between EM, GA and PSO to HFS scheduling problems, the proposed approach may be better than PSO and GA.



Figure 2. Comparison between the EM, PSO and GA for 5, 10, 15 and 20 jobs (100, 500 and 1,000 iterations)



Figure 3. Comparison between the EM, PSO and GA for N=5 jobs

D 1619

4. CONCLUSION AND PROSPETIVE ENDEAVOR

The present paper reports the results of a population-based metaheuristic approch that was originally advanced to optimize unconstrained continuous functions located on an similarity with electromagnetism concept applied to problems of HFS scheduling. We compare the simulation results of the EM algorithm applied to FSH problems with the meta-heuristics of the literature; we notice that they are very competitive. Therefore, we believe that the hybridization between EM and Tabu search could give better results by replacing the local search used by Tabu search. In the procepective, we seek to develop the accomplishement of the EM algorithm to solve combinatorial problems using parallelism techniques. Moreover, the ME algorithm can be useful for multi-objective functions.

REFERENCES

- C. Y. Lee and G. L. Vairaktarakis, "Minimizing makespan in hybrid flowshops," *Operations Research Letters*, vol. 16, no. 3, pp. 149–158, Oct. 1994, doi: 10.1016/0167-6377(94)90026-4.
- [2] M. Gourgand, N. Grangeon, and S. Norre, "A review of the static stochastic flow-shop scheduling problem," *Journal of Decision Systems*, vol. 9, no. 2, pp. 1–31, Jan. 2000, doi: 10.1080/12460125.2000.9736710.
- [3] K. Belkadi, M. Gourgand, M. Benyettou, and A. Aribi, "Sequential and parallel genetic algorithms for the hybrid flow shop scheduling problem," *Journal of Applied Sciences*, vol. 6, no. 4, pp. 775–778, Feb. 2006, doi: 10.3923/jas.2006.775.778.
- [4] D. Debels, B. De Reyck, R. Leus, and M. Vanhoucke, "A hybrid scatter search/electromagnetism meta-heuristic for project scheduling," *European Journal of Operational Research*, vol. 169, no. 2, pp. 638–653, Mar. 2006, doi: 10.1016/j.ejor.2004.08.020.
- [5] M. Gourgand, N. Grangean, and S. Norre, "Metaheuristics for deterministic hybrid flow shop problem," *Journal Européen des Systèmes Automatisés*, vol. 34, no. 9, pp. 1107–1135, 2000.
- [6] H. Morita and N. Shio, "Hybrid branch and bound method with genetic algorithm for flexible flowshop scheduling problem," JSME International Journal, Series C: Mechanical Systems, Machine Elements and Manufacturing, vol. 48, no. 1, pp. 46–52, 2005, doi: 10.1299/jsmec.48.46.
- [7] N. Qun, Z. Taijin, and M. Shiwei, "A quantum-inspired immune algorithm for hybrid flow shop with makespan criterion," *Journal of Universal Computer Science*, vol. 15, no. 4, pp. 765–785, 2009, doi: 10.3217/jucs-015-04-0765.
- [8] R. Ruiz and C. Maroto, "A genetic algorithm for hybrid flowshops with sequence dependent setup times and machine eligibility," *European Journal of Operational Research*, vol. 169, no. 3, pp. 781–800, Mar. 2006, doi: 10.1016/j.ejor.2004.06.038.
- [9] E. Taillard, "Benchmarks for basic scheduling problems," *European Journal of Operational Research*, vol. 64, no. 2, pp. 278–285, Jan. 1993, doi: 10.1016/0377-2217(93)90182-M.
- [10] L. Tang and Y. Zhang, "Heuristic combined artificial neural networks to schedule hybrid flow shop with sequence dependent setup times," in *Lecture Notes in Computer Science*, vol. 3496, no. I, Springer Berlin Heidelberg, 2005, pp. 788–793.
- [11] M. Mirabi, "A novel hybrid genetic algorithm to solve the sequence-dependent permutation flow-shop scheduling problem," *International Journal of Advanced Manufacturing Technology*, vol. 71, no. 1–4, pp. 429–437, Nov. 2014, doi: 10.1007/s00170-013-5489-5.
- [12] R. Ruiz and J. A. Vázquez-Rodríguez, "The hybrid flow shop scheduling problem," *European Journal of Operational Research*, vol. 205, no. 1, pp. 1–18, Aug. 2010, doi: 10.1016/j.ejor.2009.09.024.
- [13] Y. Xu and L. Wang, "Differential evolution algorithm for hybrid flow-shop scheduling problems," *Journal of Systems Engineering and Electronics*, vol. 22, no. 5, pp. 794–798, Oct. 2011, doi: 10.3969/j.issn.1004-4132.2011.05.011.
- [14] A. Vignier, P. Commandeur, and C. Proust, "New lower bound for the hybrid flowshop scheduling problem," in *IEEE Symposium on Emerging Technologies & Factory Automation*, ETFA, 1997, pp. 446–451, doi: 10.1109/etfa.1997.616312.
- [15] A. Vignier, J. C. Billaut, and C. Proust, "Hybrid flow-shop scheduling problems: state of the art (in France: Les problèmes d'ordonnancement de type flow-shop hybride: État de l'art)," *RAIRO - Operations Research*, vol. 33, no. 2, pp. 117–183, Apr. 1999, doi: 10.1051/ro:1999108.
- [16] J. N. D. Gupta, "Two-stage, hybrid flowshop scheduling problem," *Journal of the Operational Research Society*, vol. 39, no. 4, pp. 359–3641, Apr. 1988, doi: 10.1057/jors.1988.63.
- [17] S. I. Birbil and O. Feyziołu, "A global optimization method for solving fuzzy relation equations," in *Lecture Notes in Artificial Intelligence (Subseries of Lecture Notes in Computer Science)*, vol. 2715, Springer Berlin Heidelberg, 2003, pp. 718–724.
- [18] S. I. Birbil, S. C. Fang, and R. L. Sheu, "On the convergence of a population-based global optimization algorithm," *Journal of Global Optimization*, vol. 30, no. 2–3, pp. 301–318, Nov. 2004, doi: 10.1007/s10898-004-8270-3.
- [19] P. C. Chang, S. H. Chen, and C. Y. Fan, "A hybrid electromagnetism-like algorithm for single machine scheduling problem," *Expert Systems with Applications*, vol. 36, no. 2 PART 1, pp. 1259–1267, Mar. 2009, doi: 10.1016/j.eswa.2007.11.050.
- [20] B. Maenhout and M. Vanhoucke, "An electromagnetic meta-heuristic for the nurse scheduling problem," *Journal of Heuristics*, vol. 13, no. 4, pp. 359–385, Apr. 2007, doi: 10.1007/s10732-007-9013-7.
- [21] A. Jamili, M. A. Shafia, and R. Tavakkoli-Moghaddam, "A hybridization of simulated annealing and electromagnetism-like mechanism for a periodic job shop scheduling problem," *Expert Systems with Applications*, vol. 38, pp. 5895–5901, 2011, doi: 10.1016/j.eswa.2010.11.034.
- [22] P. Wu, K. J. Yang, and H. C. Fang, "A revised EM-like algorithm+K-OPT method for solving the traveling salesman problem," in *First International Conference on Innovative Computing, Information and Control 2006*, 2006, pp. 546–549, doi: 10.1109/ICICIC.2006.24.
- [23] A. Yurtkuran and E. Emel, "A new hybrid electromagnetism-like algorithm for capacitated vehicle routing problems," *Expert Systems with Applications*, vol. 37, no. 4, pp. 3427–3433, Apr. 2010, doi: 10.1016/j.eswa.2009.10.005.
- [24] M. M. Ali and M. Golalikhani, "An electromagnetism-like method for nonlinearly constrained global optimization," *Computers and Mathematics with Applications*, vol. 60, no. 8, pp. 2279–2285, Oct. 2010, doi: 10.1016/j.camwa.2010.08.018.
- [25] J. Y. Jhang and K. C. Lee, "Array pattern optimization using electromagnetism-like algorithm," AEU International Journal of Electronics and Communications, vol. 63, no. 6, pp. 491–496, Jun. 2009, doi: 10.1016/j.aeue.2008.04.001.
- [26] S. I. Birbil and S. C. Fang, "An electromagnetism like mechanism for global optimization," *Journal of Global Optimization*, vol. 25, pp. 263–282, 2003, doi: 10.1023/a:1022452626305.
- [27] B. Naderi, R. Tavakkoli-Moghaddam, and M. Khalili, "Electromagnetism-like mechanism and simulated annealing algorithms for flowshop scheduling problems minimizing the total weighted tardiness and makespan," *Knowledge-Based Systems*, vol. 23, no. 2, pp. 77–85, Mar. 2010, doi: 10.1016/j.knosys.2009.06.002.
- [28] Nai-Chieh Wei, "An electromagnetism-like mechanism for solving cell formation problems," *Scientific Research and Essays*, vol. 7, no. 9, Mar. 2012, doi: 10.5897/sre11.967.

- [29] C. T. Su and H. C. Lin, "Applying electromagnetism-like mechanism for feature selection," *Information Sciences*, vol. 181, no. 5, pp. 972–986, Mar. 2011, doi: 10.1016/j.ins.2010.11.008.
- [30] P. Wu, K. J. Yang, and Y. Y. Hung, "The study of electromagnetism-like mechanism based fuzzy neural network for learning fuzzy if-then rules," in *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics*), vol. 3684 LNAI, Springer Berlin Heidelberg, 2005, pp. 382–388.
- [31] P. Wu, W. H. Yang, and N. C. Wei, "An electromagnetism algorithm of neural network analysis—an application to textile retail operation," *Journal of the Chinese Institute of Industrial Engineers*, vol. 21, no. 1, pp. 59–67, Jan. 2004, doi: 10.1080/10170660409509387.

BIOGRAPHIES OF AUTHORS



Smail Khaled Solution State Stat



Djebbar Bachir b x c received doctoral degree in Mathematical Sciences from Paul Sabatier University in Toulouse, France in 1987, and Ph.D. state in mathematical approximation from the University of Science and Technology of Oran. He held several administrative positions at the Faculty of Mathematics and Computer Science at the Mohamed Boudiaf University of Technology in Oran (USTOMB), head of the Computer Science Department from 1999 to 2008, Vice Dean in charge of studies from 2008 to 2011 and Dean of the Faculty of Mathematics and Computer Science, since 2017, he is currently a professor in the Department of Computer Science. He has supervised and co-supervised more than 25 masters and 15 doctorates in Computer Science and Mathematics. He is the author or co-author of more than 48 publications: more than 95 citations. His research interests include complex analysis, approximation and optimization, computer imaging, machine learning and intelligent systems. He can be contacted at email: bachir.djebbar@univ-usto.dz.