

Energy-efficient deep Q-network: reinforcement learning for efficient routing protocol in wireless internet of things

Sampoorna Bhimshetty¹, Agughasi Victor Ikechukwu²

¹Department of Computer Science and Engineering, University of Visvesvaraya College of Engineering, Bangalore, India

²Department of Computer Science and Engineering, Maharaja Institute of Technology Mysore, Mysore, India

Article Info

Article history:

Received Oct 20, 2023

Revised Oct 29, 2023

Accepted Nov 23, 2023

Keywords:

Energy consumption

Energy-efficient routing

Network performance

Q-learning

Reinforcement learning

ABSTRACT

The internet of things (IoT) underscores pivotal real-world applications ranging from security systems to smart infrastructure and traffic management. However, contemporary IoT devices grapple with significant challenges pertaining to battery longevity and energy efficiency, constraining the assurance of prolonged network lifetimes and expansive sensor coverage. Many existing solutions, although promising on paper, are intricate and often impractical for real-world implementations. Addressing this gap, we introduce an energy-efficient routing protocol leveraging reinforcement learning (RL) tailored for wireless sensor networks (WSNs). This protocol harnesses RL to discern the optimal transmission route from the source to the sink node, factoring in the energy profile of each intermediary node. Training of the RL algorithm is facilitated through a reward function that includes energy outflow and data transmission efficacy. The model was compared against two prevalent routing protocols, LEACH and fuzzy C-means (FCM), for a comprehensive assessment. Simulation results highlight our protocol's superiority with respect to the active node count, energy conservation, network longevity, and data delivery efficiency.

This is an open access article under the [CC BY-SA](https://creativecommons.org/licenses/by-sa/4.0/) license.



Corresponding Author:

Agughasi Victor Ikechukwu

Department of Computer Science and Engineering, Maharaja Institute of Technology Mysore
Mysore, Karnataka, India

Email: victor.agughasi@gmail.com

1. INTRODUCTION

The internet of things (IoT) is a network of electronic devices that can gather, process, and share data, aiming to better current services [1]. There are many practical use cases of IoT, such as in healthcare, waste management, transportation, and more [2], [3]. Devices like radio-frequency identification (RFID) tags, mobile phones, and sensors gather data via a vast IoT network. However, these devices, often called sensor nodes, have limited computing power and short battery life. The existing approaches to direct data, or routing methods, in wireless sensor networks (WSNs) are complex and need resources like processing power and memory that many IoT devices do not have in surplus [4].

Devices in the IoT include smartphones, wireless sensors, and RFID tags, among others [5], [6]. A typical sensor has parts for power, sensing, processing, and communicating [7]–[10]. While the power part supplies energy to others, the other parts use very little energy [11]–[13]. This energy efficiency becomes paramount for devices deployed in challenging terrains and environment where frequent battery replacements or recharges are untenable [13], [14]. It is a widely accepted notion that energy-efficient routing algorithms can judiciously control the power consumption, thereby helping prolong the network's operational longevity.

Given these challenges, there is a growing demand for energy management strategies that are resource-dependent yet robust to implement. Distributing the routing process evenly across devices is pivotal

for such an energy-efficient network. This ensures balanced energy dissipation and increases the likelihood that more gadgets will keep working for longer.

In this regard, our research introduces a reinforcement learning-centric approach strategy for designing a low-power IoT routing protocol. The proposed method improves the longevity and scalability of an IoT network by balancing the energy produced in the network, and adeptly distributing energy among devices. The protocol identifies optimal transmission routes by incentivizing nodes to exchange locally pertinent data using residual energy as criteria. Furthermore, the hop count attribute was finetuned to minimize overall network latency. The following are our contributions:

- We repurpose energy optimization as a crucial part of routing concerns in the IoT landscape.
- We suggest a new routing plan that uses the least energy.
- We use a method called Q-learning to bolster energy savings further.
- Benchmarking the network efficiency against two established state-of-the-art methodologies.

The paper is in five sections: Section 2 discusses other works on power-saving routing for IoT-based WSNs. In section 3 explains the proposed methodology. The simulation setup and the ensuing results are presented in section 4. Section 5 summarizes the paper, offering concluding remarks and potential avenues for future exploration.

2. RELATED WORKS

2.1. Reinforcement learning

Reinforcement learning (RL) refers to a class of algorithms used to improve the efficiency of Markov property-based sequential decision-making [15], [16]. These algorithms operate by learning to make decisions through trial and error, essentially learning a strategy or policy that maps states of the world to the actions that should be taken in those states. The fundamental principle of RL is the concept of reward: algorithms learn to take actions that maximize cumulative reward over time. This approach makes RL especially suitable for complex environments where explicit programming of all possible scenarios is impractical. The RL paradigm can be divided into: i) model-based RL: when the model of the system is available and ii) model-free RL: when the system's model is not known.

Central to RL is the agent's interaction with the environment. As depicted in Figure 1, the agent makes decisions based on the state S_t of the environment. The agent takes an action a , and as a result of the consequence of this action, the environment transitions to a new state S_{t+1} and provides a reward R_t to the agent.




Figure 1. Reinforcement learning agent interaction

In scenarios where the return reward is not instantaneous but rather delayed, meaning that the immediate reward does not accurately reflect the agent's true performance. The cumulative reward R_t is calculated as (1):

$$R_t = r_t + \gamma r_{t+1} + \gamma^2 r_{t+2} \dots = \sum_{t=0}^{T-1} \gamma^t r_{t+1} \quad (1)$$

where γ = factor, capturing the uncertainty of future rewards. The policy can never guarantee that the same future reward will be gained by the same behaviour because of the inherent uncertainty in the environment. The primary goal of RL algorithms is to ascertain the optimal action strategy, π , $\text{argmax}(\pi)$, as described in (2):

$$\pi^+ = \operatorname{argmax}_{\xi_{\pi}} [\sum_{t=0}^{t_{max}} \gamma^t r_t] \tag{2}$$

2.2. Deep reinforcement learning with deep neural networks

Recent advances in deep learning (DL), particularly the use of deep neural networks (DNNs), have enabled the extraction of intricate patterns from high-dimensional data sources like images, audios, and videos [17]. DNNs in the context of RL, termed deep reinforcement learning (DRL), is depicted in Figure 2. DRL leverages DNNs to deduce optimal policies and extract relevant environmental data. DRL can determine either the Q-value (value-based) or predict a probability distribution of potential actions (policy-based) [18], [19].




Figure 2. DRL framework

2.3. Wireless network protocols

Wireless networks face challenges in security, reliability, and energy efficiency. Researchers have proposed different protocols to address these issues [20]–[22]. Recent advancements have also seen the integration of machine learning and game theory to factor-in the optimal routing approaches for wireless networks [23], [24]. WSNs have seen the evolution of diverse routing protocols. Kooshari *et al.* [25] classifies these into three primary categories:

- Flat routing: data-centric protocols without any constraints on data origin [26], [27].
- Location-based routing: these assign addresses to sensor nodes based on their geographical locations. Techniques include relative distance calculations from signal strengths and global positioning system (GPS)-based location tracking [28].
- Hierarchical routing: these protocols prioritize energy conservation. They distribute routing responsibilities based on the capabilities of the devices, ensuring optimal energy use [29]–[31]. Table 1 summarizes the findings of relevant literature.

Table 1. Summary table of literature

Topic	Description	References
RL basics	Algorithms for decision-making based on Markov property	[15], [16]
DRL with DNNs	Integration of deep learning with RL for high-dimensional data	[17]–[19], [32], [33]
Wireless network protocols	Protocols addressing security, reliability, and energy efficiency	[20]–[24]
WSN routing types	Classification into flat, location-based, and hierarchical routing	[25]–[31]

3. METHOD

In addressing energy efficiency challenges within IoT routing, this research employs the adaptability of RL. With RL’s potential to optimize decisions based on environmental feedback, it offers a solution for dynamic, resource-limited IoT networks. Central to the approach is an agent interacting with the IoT network, observing network states such as residual energy, data queue lengths, and traffic. To manage the high dimensionality in large-scale IoT networks, DRL is introduced, enabling the agent to extract patterns via DNNs for better policy learning. Building on this, the energy-efficient deep Q-network (EEDQN) routing protocol is proposed in Figure 3. EEDQN employs a Q-network that, using the network state, estimates Q-values for potential actions, emphasizing energy conservation. This ensures decisions that maximize long-term rewards, adapting to IoT network dynamics.




Figure 3. Overview of the proposed methodology EEDQN

3.1. Network setup and cluster formation phase

The process primarily focuses on establishing the network and selecting the cluster head, which is divided into two segments. Initially, devices determine their preliminary Q-values using inherent data. The central station disseminates a periodic signal detailing its geographical coordinates. On intercepting this signal, every device registers the central station's location and applies (1) and (2) to deduce its starting Q-value, considering the energy reserve and number of hops. It's presumed that each device possesses a unique energy reserve. A set distance boundary is maintained between the cluster heads (CHs) and the central station to streamline the network and aid distant sensors in locating a CH. To ensure efficient energy usage and direct connections towards the central station, CHs are strategically positioned away from the network's periphery, minimizing extended communication paths. The entire election process is described in Algorithm 1. Q-value computation based on energy level and hop count, as presented in (3) and (4):

$$Q(x, y) = Q_{prev}(x, y) + \beta(r + \gamma \cdot highest(Q_{next}(x', y'))) - Q(x, y) \quad (3)$$

$$\text{Energy level update } E(t + 1) = E(t) - ETx(k) - ERx(k) - EDA \quad (4)$$

where: $Q(x, y)$ =Q-value of a state-action pair; x =learning rate; r =reward for taking action y in state s . γ =discount factor; $max(Q(x', y'))$ =maximum Q-value over all possible actions x' in the next state y' . $E(t)$ =current energy level; $ETx(k)$ =energy used to transmit a packet of length k . $ERx(k)$ =energy used to receive a packet of length k . EDA is the energy consumed by the device for data aggregation.

Algorithm 1. The entire election processes

```

1. Network setup and cluster head election:
   For each device do:
       1a. SELECT a random backoff time and wait for it to expire
       1b. ASSIGN the cluster head to the device with maximum energy
       1c. BROADCAST a group head announcement message to inform other
   devices of its status.
   End For
2. Cluster Formation:
   For each device that detects a group head announcement do:
       2a. JOIN the group with the strongest signal strength.
       2b. SEND a message to the identified cluster head.
       2c. UPDATE its routing table using the local information from the
   cluster head.
   End For
3. Data Transmission:
   WHILE! Destination Node do:
       3a. SELECT the next-hop device using its routing table,
   prioritizing residual energy and position coordinates.

```

```

3b. TRANSMIT local information to the selected next-hop device.
3c. EXTRACT information from the received packet header and UPDATE
its routing table.
    End While
    Extract the information encapsulated in the packet header
and UPDATE its routing table.
4. Reinforcement learning:
    4a. EVALUATE the energy efficiency of routing decisions based on energy
consumption and packet transmission distance.
    4b. UPDATE routing decisions using a Q-learning algorithm to optimize
future choices.
    
```

3.2. Data transmission phase

In the phase of data transmission, each device harnesses RL to maximize its routing decisions. This adaptive decision-making process involves recalculating the Q-value, considering both immediate rewards from recent actions and the anticipated cumulative rewards. The methodology encompasses three integral components: a model estimating energy usage, a function that determines rewards, and a mechanism to refine the Q-value. The energy model gauges the remaining energy, adjusting for energy expended during packet transfers. Using this updated energy data alongside the hop count, the system computes the reward. This reward subsequently informs the Q-value recalibration, as detailed in (5) to (7). Equation for updating Q-value:

$$Q(s, a) = Q(s, a) + \alpha(r + \gamma \max(Q(s', a')) - Q(s, a)) \tag{5}$$

in (6) for energy consumption model:

$$E(t + 1) = E(t) - ETx(k) - ERx(k) - EDA \tag{6}$$

in (7) for reward function:

$$r = Reward(E(t + 1), h) \tag{7}$$

where:

$Q(s,a)$ =Q-value of a state-action pair

α =learning rate

r =the immediate reward obtained from taking action a in state s

γ =the discount factor

$\max(Q(s',a'))$ =the maximum Q-value over all possible actions a' in the next state s'

$E(t)$ =the current energy level

$ETx(k)$ =the energy used to transmit a packet of length k

$ERx(k)$ =the energy used to receive a packet of length k

EDA =the energy consumed by the device for data aggregation

h =the hop count

3.2. Reinforcement learning

3.2.1. Reward function

This metric is obtained by evaluating the remaining energy, denoted as Lr, and the aggregate of hops, represented by Nhops:

$$Reward = g(Lr, Nhops) \tag{8}$$

where g =reward function. In this stage, the proximity between the transmitting device and its neighboring devices is also taken into account. The span between a device, labeled Si, and the central station through a connecting device, Sj, is labeled as Dlink and is determined as per (9):

$$Dlink = \text{sqrt}((xi - xj)^2 + (yi - yj)^2 + (zi - zj)^2) \tag{9}$$

where xi, yi, and zi=the coordinates of device Si and xj, yj, and zj are the coordinates of device Sj. The estimated hop count is computed as (10):

$$Nh = Dlink / (TXrange) \tag{10}$$

where $TXrange$ is the transmission range. The reward function is then computed as:

$$Reward = Er - a * Nh \quad (11)$$

where a is a constant that determines the trade-off between energy consumption and hop count.

3.2.2. Q-value update

To ascertain the true worth of a specific action, it is essential to calculate the action-value function. This function gauges the efficacy of executing a certain action in a designated state while adhering to a strategy denoted by π . The function is calculated as a discounted total of rewards received by the agent post specific action in a given state. This can be mathematically represented in (12):

$$Q(s, a) = E[Rt + 1 + \gamma Rt + 2 + \gamma^2 Rt + 3 + \dots | St = s, At = a, \pi] \quad (12)$$

where:

$Q(s,a)$ =the action-value function for taking action 'a' in state 's'

E =the expectation operator

Rt =the reward received at time 't'

γ (gamma)=the discount factor used to balance immediate and future rewards

St =the current state of the agent

At =the action taken by the agent in the current state

π =the policy being followed by the agent

4. RESULTS AND DISCUSSION

4.1. Model training and implementation

Training the EEDQN network entails using past data from the IoT network alongside simulated scenarios. This ensures robustness in the learned policies. The model is trained iteratively, with each episode involving. Observing the current state, taking an action based on the Q-network, receiving a reward from the environment, and adjusting the Q-network based on the observed reward using backpropagation.

We performed simulations in Python 3.10 to validate the effectiveness of the model. 120 devices were randomly distributed over a sensing field of 150 m×150 m. The sub station was positioned at the center of the sensing field with coordinates of (75, 75). The network was designed with diversity in mind, featuring devices that have energy capacities spanning between 1 and 2 joules. The simulation parameters are detailed in Table 2.

Table 2. Simulation parameters and corresponding values

Parameters	Values
a	1.00
γ	0.92
h	20
Field size	150 m×150 m
Sum of devices	120
Initial energy	1.5 joules

The suggested protocol incorporates two crucial metrics: the hop count and the remaining energy. Additionally, probabilistic values, denoted as 'a' and 'b', play a role. The choice of a device hinges on its energy status and hop count. When 'a' has a larger value, devices with abundant energy are more likely to be chosen. Conversely, a greater 'b' value favors devices that have fewer hops to the primary station. Figure 4 provides the results of the initialization of nodes using the RL approach, while Figure 5, showcasing the simulation results with parameters set at $a=0.3$, and $b=0.7$ demonstrates the protocol's optimal performance.

Remarkably, the best performance was reached with fewer than 35 operating nodes, highlighting the efficiency of our approach. This is particularly evident when assessing the energy consumption metrics, as depicted in Figures 6 and 7. The cumulative energy consumed tends to decrease as the sum of nodes increases, this effect is captured in Figure 7.




Figure 4. RL-based node initialization




Figure 5. Effects on performance ($a=0.3, b=0.7$)




Figure 6. Cluster-based energy consumption




Figure 7. RL-based energy consumption

An assessment was conducted against established clustering protocols. Key performance indicators included energy consumption per operational round and the duration of sustained network activity before energy depletion, using state of the art (SoTA) clustering protocols like LEACH, HEED, and smart-BEE [34]. We used two metrics for comparison: i) network area per round which also helps evaluate the network lifetime and ii) energy consumed by all devices each round. In Figure 8, we assessed the network efficiency by varying the number of sensor devices used.




Figure 8. Proposed method comparison with SoTA

To improve the network lifetime and avoid the challenges associated with a cold start, a cluster-based routing protocol with RL was incorporated [35]. The learning rate α set to 1 accelerates the learning process, which resulted in a significant reduction in energy consumption per round. Additionally, by setting the discount factor γ to 0.92, we were able to prioritize future rewards, which contributed to better balancing of energy consumption over time, minimizing energy consumption per device, and ultimately extending the network lifetime, as demonstrated in Figure 7.

The consequent energy distribution, as illustrated in Figure 8, underscores the protocol’s efficiency, yielding enhanced energy efficiency and a more extended network operational span. Such advancements underscore the potential benefits for enterprises and researchers, highlighting avenues for optimizing IoT network efficiency and reduce energy costs. Table 3 provides a comparative analysis of the proposed approach.

Table 3. Comparative analysis with state-of-the-art protocols

Metrics (average over 50 rounds)	Proposed protocol	LEACH	HEED	Smart-BEE
Network area per round (m ²)	11,250	9,750	10,500	9,800
Energy consumed per round (Joules)	1.1	1.5	1.4	1.6

From Table 3, the following implications and observations can be drawn: the proposed protocol demonstrates superior area coverage, registering 11,250 m² per round and outpacing LEACH, HEED, and smart-BEE by significant margins. It also excels in energy efficiency, consuming only 1.1 Joules per round, notably less than its counterparts. This efficiency translates to extended device battery life and network longevity. Moreover, the protocol's expansive coverage and low energy consumption highlight its operational efficacy. It promises scalability, maintaining performance as network size grows [36]. When compared to the established protocols like LEACH, HEED, and Smart-BEE, the proposed protocol's advantages become evident, underscoring the benefits of integrating reinforcement learning with a cluster-based routing approach [37].

5. CONCLUSION

This research introduced an RL-based routing protocol for IoT aimed at optimizing energy consumption and extending network lifespan. By leveraging initial energy and hop count, the protocol effectively determined the optimal route for data transmission. Through a multi-phased approach, including cluster formation and data transmission, reinforcement learning was employed to prioritize energy-efficient routing. Comparison with existing protocols like LEACH, smart-BEE, and HEED validated the superior energy efficiency and longevity of the proposed method. The result further showcased the protocol's suitability for modern IoT networks, emphasizing its balance between sustainability and reach. An extension of this work will explore additional parameters, like network traffic and node mobility, and the possibility of incorporating other deep learning techniques to refine the protocol.

REFERENCES

- [1] L. Farhan and R. Kharel, "Internet of things: vision, future directions and opportunities," in *Smart Sensors, Measurement and Instrumentation*, vol. 29, 2019, pp. 331–347.
- [2] A. Altieri, P. Piantanida, L. R. Vega, and C. G. Galarza, "On fundamental trade-offs of device-to-device communications in large wireless networks," *IEEE Transactions on Wireless Communications*, vol. 14, no. 9, pp. 4958–4971, Sep. 2015, doi: 10.1109/TWC.2015.2430341.
- [3] N. Nasser, L. Karim, A. Ali, M. Anan, and N. Khelifi, "Routing in the internet of things," in *2017 IEEE Global Communications Conference, GLOBECOM 2017 - Proceedings*, Dec. 2017, vol. 2018-January, pp. 1–6, doi: 10.1109/GLOCOM.2017.8253955.
- [4] R. Zagrouba and A. Kardi, "Comparative study of energy efficient routing techniques in wireless sensor networks," *Information (Switzerland)*, vol. 12, no. 1, pp. 1–28, Jan. 2021, doi: 10.3390/info12010042.
- [5] S. Ghosh, "A cognitive routing framework for self-organized knowledge-defined networks," School of Engineering, London South Bank University, 2022.
- [6] S. Li, L. Da Xu, and S. Zhao, "The internet of things: a survey," *Information Systems Frontiers*, vol. 17, no. 2, pp. 243–259, Apr. 2015, doi: 10.1007/s10796-014-9492-7.
- [7] A. Singh, S. Sharma, and J. Singh, "Nature-inspired algorithms for wireless sensor networks: a comprehensive survey," *Computer Science Review*, vol. 39, p. 100342, Feb. 2021, doi: 10.1016/j.cosrev.2020.100342.
- [8] H. M. A. Fahmy, "WSNs applications," in *Signals and Communication Technology*, 2023, pp. 67–242.
- [9] T. M. Ghazal, M. K. Hasan, H. M. Alzoubi, M. Alshurideh, M. Ahmad, and S. S. Akbar, "Internet of things connected wireless sensor networks for smart cities," in *Studies in Computational Intelligence*, vol. 1056, 2023, pp. 1953–1968.
- [10] D. Kandris, E. A. Evangelakos, D. Rountos, G. Tselikis, and E. Anastasiadis, "LEACH-based hierarchical energy efficient routing in wireless sensor networks," *AEU - International Journal of Electronics and Communications*, vol. 169, p. 154758, Sep. 2023, doi: 10.1016/j.aeue.2023.154758.
- [11] S. Zahir *et al.*, "Robust counting in overcrowded scenes using batch-free normalized deep ConvNet," *Computer Systems Science and Engineering*, vol. 46, no. 3, pp. 2741–2754, 2023, doi: 10.32604/csse.2023.037706.
- [12] H. Kathiriya, A. Bavarva, and V. Sorathiya, "Low-energy network protocols," *Recent Trends and Best Practices in Industry 4.0*, pp. 283–308, 2023, doi: 10.1201/9781003441717-11.
- [13] A. V. Ikechukwu and S. Murali, "CX-Net: an efficient ensemble semantic deep neural network for ROI identification from chest-x-ray images for COPD diagnosis," *Machine Learning: Science and Technology*, vol. 4, no. 2, p. 025021, Jun. 2023, doi: 10.1088/2632-2153/acd2a5.
- [14] S. He, Q. Li, M. Khishe, A. S. Mohammed, H. Mohammadi, and M. Mohammadi, "The optimization of nodes clustering and multi-hop routing protocol using hierarchical chimp optimization for sustainable energy efficient underwater wireless sensor networks," *Wireless Networks*, Aug. 2023, doi: 10.1007/s11276-023-03464-9.
- [15] M. Rao and N. K. Kamila, "Spider monkey optimisation based energy efficient clustering in heterogeneous underwater wireless sensor networks," *International Journal of Ad Hoc and Ubiquitous Computing*, vol. 29, no. 1–2, pp. 50–63, 2018, doi: 10.1504/ijahuc.2018.094397.
- [16] A. V. Ikechukwu, S. Murali, and B. Honnaraju, "COPDNet: an explainable ResNet50 model for the diagnosis of COPD from CXR images," in *2023 IEEE 4th Annual Flagship India Council International Subsections Conference: Computational Intelligence and Learning Systems, INDISCON 2023*, Aug. 2023, pp. 1–7, doi: 10.1109/INDISCON58499.2023.10270604.
- [17] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "ImageNet classification with deep convolutional neural networks," *Advances in Neural Information Processing Systems*, vol. 2, pp. 1097–1105, 2012.
- [18] A. V. Ikechukwu and S. Murali, "i-Net: a deep CNN model for white blood cancer segmentation and classification," *International Journal of Advanced Technology and Engineering Exploration*, vol. 9, no. 95, pp. 1448–1464, Oct. 2022, doi: 10.19101/IJATEE.2021.875564.
- [19] A. V. Ikechukwu, S. Murali, R. Deepu, and R. C. Shivamurthy, "ResNet-50 vs VGG-19 vs training from scratch: a comparative analysis of the segmentation and classification of pneumonia from chest X-ray images," *Global Transitions Proceedings*, vol. 2, no. 2, pp. 375–381, Nov. 2021, doi: 10.1016/j.glt.2021.08.027.

- [20] R. Subramanyam, Y. A. Jancy, and P. Nagabushanam, "Cooperative optimization techniques in distributed MAC protocols – a survey," *International Journal of Pervasive Computing and Communications*, Oct. 2023, doi: 10.1108/IJPC-07-2022-0256.
- [21] A. Iftikhar, K. N. Qureshi, M. Shiraz, and S. Albahli, "Security, trust and privacy risks, responses, and solutions for high-speed smart cities networks: a systematic literature review," *Journal of King Saud University - Computer and Information Sciences*, vol. 35, no. 9, p. 101788, Oct. 2023, doi: 10.1016/j.jksuci.2023.101788.
- [22] Z. Zheng, S. Jiang, R. Feng, L. Ge, and C. Gu, "Survey of reinforcement-learning-based MAC protocols for wireless Ad Hoc networks with a MAC reference model," *Entropy*, vol. 25, no. 1, p. 101, Jan. 2023, doi: 10.3390/e25010101.
- [23] J. Liu, J. Wen, Y. Xie, L. Lin, and W. Zhou, "Social-aware D2MD user grouping based on game theory and deep Q-learning," *Peer-to-Peer Networking and Applications*, vol. 16, no. 2, pp. 606–628, Mar. 2023, doi: 10.1007/s12083-022-01411-7.
- [24] S. P. A. Kumar and H. K. Thakur, "Performance study of various routing protocols in opportunistic IoT networks," *Computational Intelligence in Analytics and Information Systems*, pp. 233–248, 2023, doi: 10.1201/9781003332367-21.
- [25] A. Kooshari, M. Fartash, P. Mihanhezahad, M. Chahardoli, J. A. Torkestani, and S. Nazari, "An optimization method in wireless sensor network routing and IoT with water strider algorithm and ant colony optimization algorithm," *Evolutionary Intelligence*, Apr. 2023, doi: 10.1007/s12065-023-00847-x.
- [26] W. A. Shutnan, M. Y. Hassan, A. H. Najim, and N. Faisal, "A review: routing challenges in wireless sensor network," in *AICCIT 2023 - Al-Sadiq International Conference on Communication and Information Technology*, Jul. 2023, pp. 40–43, doi: 10.1109/AICCIT57614.2023.10218220.
- [27] J. Wang, Y. Liu, S. Rao, X. Zhou, and J. Hu, "A novel self-adaptive multi-strategy artificial bee colony algorithm for coverage optimization in wireless sensor networks," *Ad Hoc Networks*, vol. 150, p. 103284, Nov. 2023, doi: 10.1016/j.adhoc.2023.103284.
- [28] L. A. T. Vu, Z. Bi, D. Mueller, and N. Younis, "Modular self-configurable robots-the state of the art," *Actuators*, vol. 12, no. 9, p. 361, Sep. 2023, doi: 10.3390/act12090361.
- [29] N. Duy Tan, D. N. Nguyen, H. N. Hoang, and T. T. H. Le, "EEGT: energy efficient grid-based routing protocol in wireless sensor networks for IoT applications," *Computers*, vol. 12, no. 5, p. 103, May 2023, doi: 10.3390/computers12050103.
- [30] M. S. Muthukkumar and S. Diwakaran, "Stochastic diffusion hunt optimization for potential load balancing in wireless sensor networks," *Materials Today: Proceedings*, Feb. 2023, doi: 10.1016/j.matpr.2023.02.019.
- [31] J. Hu, J. Li, H. Yan, and H. Liu, "Optimized distributed filtering for saturated systems with amplify-and-forward relays over sensor networks: a dynamic event-triggered approach," *IEEE Transactions on Neural Networks and Learning Systems*, pp. 1–12, 2023, doi: 10.1109/TNNLS.2023.3308192.
- [32] V. I. Agughasi and M. Srinivasiah, "Semi-supervised labelling of chest x-ray images using unsupervised clustering for ground-truth generation," *Applied Engineering and Technology*, vol. 2, no. 3, pp. 188–202, Sep. 2023, doi: 10.31763/aet.v2i3.1143.
- [33] A. V. Ikechukwu, P. Sreyas, A. Sena, H. Preetham, and K. Raksha, "Explainable deep learning model for covid-19 diagnosis," *IRJMETS*, vol. 4, no. 7, pp. 3051–3059, 2022.
- [34] M. Y. Hasan and D. J. Kadhim, "A new smart approach of an efficient energy consumption management by using a machine-learning technique," *Indonesian Journal of Electrical Engineering and Computer Science (IJECS)*, vol. 25, no. 1, pp. 68–78, Jan. 2022, doi: 10.11591/ijeecs.v25.i1.pp68-78.
- [35] M. Ahmed, M. Salleh, M. I. Channa, and M. F. Rohani, "Review on localization based routing protocols for underwater wireless sensor network," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 7, no. 1, pp. 536–541, Feb. 2017, doi: 10.11591/ijece.v7i1.pp536-541.
- [36] D. K. Panda and R. K. Dash, "Reliability evaluation and analysis of mobile Ad Hoc networks," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 7, no. 1, pp. 479–485, Feb. 2017, doi: 10.11591/ijece.v7i1.pp479-485.
- [37] S. Q. Ameen and R. C. Muniyandi, "Improvement at network planning using heuristic algorithm to minimize cost of distance between nodes in wireless mesh networks," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 7, no. 1, pp. 309–315, Feb. 2017, doi: 10.11591/ijece.v7i1.pp309-315.

BIOGRAPHIES OF AUTHORS



Sampoorna Bhimshetty     received her Bachelor of Engineering (B.E.) degree from VTU University, Belgaum in Computer Science in 2014, and currently pursuing her M.Tech. in Computer Science from Bangalore University-India. From 2014 to 2016, she was a Junior Software developer in Tech Narayana Software Pvt Ltd. Bangalore- India. From 2019 to 2020, she was a faculty in KLE S. Nijalingappa College in Bangalore-India. Since 2022, she is working as a faculty in AVK group of Institutions in Bangalore-India. Her research interest includes efficient routing protocol in wireless IoT, computer vision and deep learning. She can be contacted at email: sampoornabhim23@gmail.com.



Agughasi Victor Ikechukwu     received his Bachelor of Science (B.Sc.) degree from the Michael Okpara University of Agriculture Umudike-Nigeria in 2010, and Masters (M.Sc.) degree from Bangalore University, India in 2016 and currently pursuing his Ph.D. in Computer Science from the University of Mysore-India. He has authored 7 research articles, conducted 12 workshops in deep learning, and has an educational YouTube channel (Victor's Portal) where he shares his ideas on python for machine learning. His research interest includes medical image processing, computer vision and deep learning. He was a recipient of the best graduating student award of 2016 batch and holds a gold medal in computer science during his master's degree, a student member of IEEE, and a recipient of the best paper award at the international conference on computing system and its applications in 2021. He can be contacted at email: victor.agughasi@gmail.com.