

Smart panel design for renewable energy generation

Rudi Syahputra, Nelly Safitri, Fauzan, Yassir, Teuku Hasanuddin, Akhyar, Radhiah, Zulfikar

Department of Electrical Engineering, Politeknik Negeri Lhokseumawe, Aceh, Indonesia

Article Info

Article history:

Received Jan 26, 2026

Revised Jun 2, 2026

Accepted Jun 27, 2026

Keywords:

Haiwell cloud

IoT

Programmable logic controller

Smart panel

Solar power generation

ABSTRACT

The aim of this study is to design and develop a smart panel module specifically for solar power generation, which includes three critical functions: the automatic transfer switch (ATS), the automatic main failure (AMF), and capabilities for remote monitoring and control. The ATS and AMF features employ Haiwell AT12MOT Ethernet PLC control equipment in conjunction with the Haiwell B7H Ethernet IoT cloud HMI, both designed for remote operation through an IoT system and integrated with the Haiwell cloud application. The developed PLC program interacts with HMI software that is created using NB designer. Inputs from the PLC are monitored and managed via the Haiwell cloud application, which connects with the relay designated as input for the Haiwell AT12MOT PLC. The resulting design interfaces with the PLC output located within an electrical panel specifically designed to handle industrial loads. This research results in a smart panel capable of operating in an industrial context with a power capacity of 2,200 VA. It is noteworthy that during automatic operations, load transfers between solar power systems and PLN (the national grid company of Indonesia) do not occur instantaneously; instead, there is a delay of 10 seconds as the system stabilizes back to normal conditions.

This is an open access article under the [CC BY-SA](https://creativecommons.org/licenses/by-sa/4.0/) license.



Corresponding Author:

Nelly Safitri

Department of Electrical Engineering, Politeknik Negeri Lhokseumawe

Banda Aceh-Medan Street Km. 280, Buketrata, Lhokseumawe, Aceh, Indonesia

Email: nellysafitri@pnl.ac.id

1. INTRODUCTION

The implementation of solar power plants within industrial settings is increasingly promoted, particularly to enhance the efficiency of electrical energy by harnessing available energy sources in proximity to the industry. The transmission of electrical energy from the solar power plant to various loads occurs through an electrical panel, which serves as a hub for control and monitoring. The necessity for control and monitoring arises from the fact that operational conditions are not always stable or typical [1]. Control panels can be operated either manually or automatically, allowing operators to manage them from both nearby locations and remote distances. Consequently, the development of a smart panel is essential for the effective control and monitoring of the solar power plant system [2], [3].

The electrical energy generated by solar modules cannot be automatically monitored via the internet; rather, it can solely be controlled and observed through a system implemented within the solar power plant environment [4], [5]. The application of internet of things (IoT) technology is crucial for the remote control and monitoring of smart panels. There is a need for a tool that facilitates direct and remote management of electric power usage, particularly through an Android application utilizing the IoT framework [6]. It remains prevalent for this IoT system to incorporate a microcontroller, while in industrial applications, control systems typically employ programmable logic controllers (PLC) alongside human-machine interfaces (HMI) as control panels and display systems [7], [8]. This applies to both on-grid

photovoltaic power systems [9] and off-grid photovoltaic power systems [10]. Various studies addressing the implementation of IoT in solar power plants through smart panel control and monitoring systems have been documented in research conducted by authors in [11]-[13].

While previous research has focused on the intelligent management and oversight of solar power plants through IoT methodologies, the specific approaches employed have varied significantly. One study developed a system that enables wireless monitoring of photovoltaic energy generation utilizing a Raspberry Pi 3 [14]. Another investigation addressed the challenges of real-time surveillance of photovoltaic systems and the regulation of electricity supply for smart microgrid-PV applications through IoT technology [15]. Furthermore, a different study implemented photovoltaic panels as sources of electrical energy by leveraging IoT-based solutions with a PLC [16].

This research is focused on fulfilling the requirements of our partner, CV. Cotindo Jaya [17], which specializes in designing and manufacturing IoT-based smart control panels. The objective is to develop an IoT-based smart control panel that effectively addresses the implementation needs of the partners while satisfying customer demands for such technology. The development process involves programming the PLC, which interacts with HMI software developed using NB designer [18]. Inputs from the PLC are managed and monitored through the Haiwell cloud application [19], which connects to the relay designated as input for the Haiwell AT12MOT PLC [20].

2. METHOD

By identifying the requirements and technical specifications necessary for the development of intelligent control panels designed to manage solar power plants, it will assess both the essential materials needed for constructing these smart panels and the IoT components required for their remote operation and monitoring within a solar energy framework.

The project includes the design and implementation of a Haiwell AT12MOT Ethernet smart panel PLC intended for use in solar power plant management. Additionally, it encompasses the creation of graphical user interfaces (GUIs) for the Haiwell B7H Ethernet IoT cloud [21] smart panels, which facilitate control over solar energy systems. An IoT application program will be developed for use with the Blynk platform [22], further enhancing the functionality of smart panel applications in solar power generation. Moreover, this research will involve designing the visual interface of the IoT application on the Blynk platform [23], specifically for solar power plants. The effectiveness of these intelligent control panels will be evaluated through rigorous testing procedures in an IoT-based environment. Finally, this investigation will culminate in a scientific article that addresses advancements in smart control panels tailored for IoT applications in solar energy systems.

The smart control panel system at a solar power plant consists of several components, as illustrated in the block diagram in Figure 1. The block diagram explains how the smart panel connects to both local operators (via HMI) and remote users (via IoT cloud through the internet) [24]. It illustrates the interaction between the solar power plant, the PLC control system, and the remote monitoring/operation platform.




Figure 1. Block diagram of smart panel control

In order to facilitate the construction of an intelligent control panel, it is essential to establish a power circuit that serves as a reference for the wiring process involved in creating an IoT-based solar power plant smart control panel, as illustrated in Figure 2. It represents the electrical wiring concept inside the smart panel that manages the power flow between PLN (grid) and the solar power plant to supply the load. The PLC-controlled automatic transfer switch/automatic main failure (ATS/AMF) circuit and the load connection [25]. The circuit ensures stable, safe, and automatic switching between grid and solar power sources, either manually (push button/HMI) or automatically (PLC logic).




Figure 2. Wiring diagram of smart power circuit

3. RESULTS AND DISCUSSION

The physical and visual characteristics of the proposed smart panel are illustrated in Figure 3. In terms of its physical composition, the smart panel functions as an electrical enclosure that houses a PLC, relays, an HMI, an IoT module, contactors, switches, and indicators. Visually, it features a touchscreen HMI along with an IoT dashboard, enabling operators to oversee system status, modify settings, and manage operations either manually or automatically.



Figure 3. Physical appearance of the smart panel box

3.1. Design and create a Haiwell AT12MOT

The Haiwell AT12MOT PLC's input-output configuration is designed for ATS and AMF applications. The focus of the ladder diagram design for the Haiwell AT12MOT PLC is to establish a functional system that operates as an ATS/AMF. In this context, the ladder logic governs all components within the ATS/AMF circuit. The programming of the Haiwell AT12MOT PLC, which serves in the capacity of an ATS/AMF for solar power generation, adheres to the addressing conventions previously outlined.

Subsequently, a ladder diagram is developed, illustrating how the intelligent panel transitions automatically or manually between solar power and the PLN grid (ATS/AMF). Inputs such as grid status and control buttons dictate outputs like contactor relays, facilitating seamless power transfer and monitoring. Consequently, based on specific input conditions—such as grid availability, operational mode (automatic/manual), and solar energy availability—the ladder logic activates the appropriate relays to alternate between PLN and solar energy supply.

3.2. Display designs for HMI Haiwell B7H Ethernet IoT cloud smart panels

The design of the Haiwell B7H HMI display encompasses several stages, which are outlined as follows: i) The ATS/AMS monitoring stage is responsible for overseeing the automated operations of the system. This feature enables operators to easily track the status of the PLN interlock, identify which power source is active, and ascertain the condition of the utilized interlock. A key aspect of monitoring in this phase involves AMF functionality for automatic systems; ii) The ATS/AMF configuration allows for the adjustment of delay times tailored to both the generator and the existing electrical infrastructure; and iii) The ATS/AMF can function either through manual operation or automatically.

Figure 4 presents the design of the HMI developed for overseeing and managing the functionalities of smart panels within the solar–PLN system. This system encompasses capabilities for monitoring, configuration, and operation of ATS/AMF. It visually represents the operational status of the system, indicating whether it is drawing power from PLN or solar sources, provides options for modifying parameters such as delay times, and allows operators to toggle between manual and automatic modes. The graphical interface on the touchscreen serves as the primary interaction point for operators. The configuration of the Haiwell B7H HMI focuses on three essential functions: monitoring, settings, and operation of ATS/AMF. It features user-friendly graphical indicators, adjustable delay settings, and controls that support both manual and automated operations. Additionally, its integration with IoT technology facilitates local touch control alongside remote monitoring via a smartphone application linked to the smart panel in conjunction with the solar power plant.




Figure 4. HMI visual layout

The evaluation of current and voltage parameters in the smart panel utilizes incandescent lamps, each with a power rating of 200 watts. This load is structured into three phases consisting of five separate groups. Each phase accommodates a total load of 1,000 watts, with each group designated to handle a load of 200 watts. Measurements for current and voltage are carried out for both phase-to-phase and phase-to-neutral arrangements. Load increments are introduced according to the group distributions across all phases, specifically increasing by 200 watts per phase, culminating in a total addition of 600 watts for three-phase configurations. Assessments of current and voltage for the loads on the smart control panel are conducted through both manual and automated methods, which include: i) control via a push button situated on the door panel; ii) control using a touch interface on the HMI screen integrated within the panel; and iii) control through remote access facilitated by an IoT system operated via smartphone.

The assessment of the parameters related to the smart panel, which facilitates the management of solar power plant systems through push buttons. The findings obtained from the measurements and evaluations regarding the performance of the smart panel module in controlling the solar power plant

system—specifically via the push button located on the panel door—are presented in Tables 1 and 2 for the manual and automatic methods, respectively.

Table 1. Measured parameters when smart panel is operated manually

Description	On	Off	Power			Voltage						Current		
			R (W)	S (W)	T (W)	RS (V)	ST (V)	TR (V)	RN (V)	TN (V)	SN (V)	R (A)	S (A)	T (A)
PLN	X2=0	X3=1	0	0	0	0	0	0	0	0	0	0	0	0
			200	200	200	0	0	0	0	0	0	0	0	0
	X2=1	X3=0	0	0	0	385	391	386	220	225	229	0	0	0
			200	200	200	385	391	387	221	225	228	0,8	1	0,8
			400	400	400	384	390	386	220	224	228	1,7	2	1,6
			600	600	600	384	389	385	219	224	228	2,5	2	2,4
Solar power plant	X8=0	X9=1	800	800	800	383	389	384	219	223	227	3,4	3	3,3
			1000	1000	1000	382	388	384	219	223	227	4,2	4	4,1
			0	0	0	0	0	0	0	0	0	0	0	0
			200	200	200	0	0	0	0	0	0	0	0	0
	X8=1	X9=0	0	0	0	388	392	388	222	227	229	0	0	0
			200	200	200	387	392	389	222	226	229	0,8	1	0,8
			400	400	400	386	391	386	222	225	228	1,7	2	1,6
			600	600	600	386	390	386	221	225	228	2,4	2	2,3
			800	800	800	385	390	384	221	224	227	3,2	3	3,1
			1000	1000	1000	385	389	384	220	224	227	4	4	3,9

Table 2. Measured parameters when smart panel is operated automatically

Description	On	Off	Power			Voltage						Current			Information
			R (W)	S (W)	T (W)	RS (V)	ST (V)	TR (V)	RN (V)	TN (V)	SN (V)	R (A)	S (A)	T (A)	
PLN	0	1	0	0	0	0	0	0	0	0	0	0	0	0	Auto switch when the solar power plant goes off Delay 10 seconds after the system returns to normal
			200	200	200	0	0	0	0	0	0	0	0	0	
	1	0	0	0	0	385	391	386	220	225	229	0	0	0	
			200	200	200	385	391	387	221	225	228	0,8	0,8	0,8	
			400	400	400	384	390	386	220	224	228	1,7	1,6	1,6	
			600	600	600	384	389	385	219	224	228	2,5	2,4	2,4	
Solar power plant	0	1	800	800	800	383	389	384	219	223	227	3,4	3,3	3,3	Auto switch when PLN goes out Delay 10 seconds after the system returns to normal
			1000	1000	1000	382	388	384	219	223	227	4,2	4,1	4,1	
			0	0	0	0	0	0	0	0	0	0	0	0	
			200	200	200	0	0	0	0	0	0	0	0	0	
	1	0	0	0	0	388	392	388	222	227	229	0	0	0	
			200	200	200	387	392	389	222	226	229	0,8	0,8	0,8	
			400	400	400	386	391	386	222	225	228	1,7	1,6	1,6	
			600	600	600	386	390	386	221	225	228	2,4	2,3	2,3	
			800	800	800	385	390	384	221	224	227	3,2	3,1	3,1	
			1000	1000	1000	385	389	384	220	224	227	4	3,9	3,9	

Table 1 demonstrates the effective operation of the manual mode of the smart panel. It verifies that both PLN and solar energy sources can reliably support loads of up to 1,000 W per phase, maintaining consistent voltage and proportional current when controlled through the push buttons on the panel. Table 2 confirms that the ATS/AMF automation system within the smart panel functions efficiently. This system is engineered to automatically switch between PLN and solar power in the event of a failure, incorporating a 10-second pause before resuming normal operation, while ensuring stable voltage and current performance across a range of load conditions. Next, the designed smart panel for managing the solar power plant system via touch interaction on the HMI screen located on the panel door is presented in Tables 3 and 4. The data indicates that the smart panel operates efficiently in both scenarios, whether controlled manually through the HMI or in an automatic ATS/AMF mode. The key difference between these operational modes lies in user convenience and dependability.

The system was managed via a smartphone using an IoT remote control, incorporating both manual and automatic approaches, as illustrated in Tables 5 and 6. These tables indicate that the reliability of the IoT remote control closely matches that of local control, evidenced by consistent voltage and current measurements. According to Table 5, there exists a minor delay of approximately five seconds attributable to network communication. Furthermore, Table 6 enhances the automation capabilities of the PLC's ATS/AMF,

allowing for hands-free operation while still providing users with the option to monitor and assume manual control through smartphone applications.

Table 3. Measured parameters when HMI screen is touched manually

Description	On	Off	Power			Voltage						Current		
			R (W)	S (W)	T (W)	RS (V)	ST (V)	TR (V)	RN (V)	TN (V)	SN (V)	R (A)	S (A)	T (A)
PLN	M10=0	M11=1	0	0	0	0	0	0	0	0	0	0	0	0
			200	200	200	0	0	0	0	0	0	0	0	0
	M10=1	M11=10	0	0	0	385	391	386	220	225	229	0	0	0
			200	200	200	385	391	387	221	225	228	0,8	0,8	0,8
			400	400	400	384	390	386	220	224	228	1,7	1,6	1,6
			600	600	600	384	389	385	219	224	228	2,5	2,4	2,4
Solar power plant	M20=0	M21=1	800	800	800	383	389	384	219	223	227	3,4	3,3	3,3
			1000	1000	1000	382	388	384	219	223	227	4,2	4,1	4,1
	M20=1	M21=0	0	0	0	0	0	0	0	0	0	0	0	0
			200	200	200	0	0	0	0	0	0	0	0	0
			0	0	0	388	392	388	222	227	229	0	0	0
			200	200	200	387	392	389	222	226	229	0,78	0,78	0,78
			400	400	400	386	391	386	222	225	228	1,65	1,58	1,58
			600	600	600	386	390	386	221	225	228	2,35	2,25	2,25
			800	800	800	385	390	384	221	224	227	3,2	3,1	3,1
			1000	1000	1000	385	389	384	220	224	227	4	3,9	3,9

Table 4. Measured parameters when the HMI screen is touched automatically

Description	On	Off	Power			Voltage						Current			Information
			R (W)	S (W)	T (W)	RS (V)	ST (V)	TR (V)	RN (V)	TN (V)	SN (V)	R (A)	S (A)	T (A)	
PLN	0	1	0	0	0	0	0	0	0	0	0	0	0	0	Auto switch when the solar power plant goes off
			200	200	200	0	0	0	0	0	0	0	0	0	
	1	0	0	0	0	385	391	386	220	225	229	0	0	0	Delay 10 seconds after the system returns to normal
			200	200	200	385	391	387	221	225	228	1	1	1	
			400	400	400	384	390	386	220	224	228	2	2	2	
			600	600	600	384	389	385	219	224	228	3	2	2	
Solar power plant	0	1	800	800	800	383	389	384	219	223	227	3	3	3	Auto switch when PLN goes out
			1000	1000	1000	382	388	384	219	223	227	4	4	4	
	1	0	0	0	0	0	0	0	0	0	0	0	0	0	Delay 10 seconds after the system returns to normal
			200	200	200	0	0	0	0	0	0	0	0	0	
			0	0	0	388	392	388	222	227	229	0	0	0	
			200	200	200	387	392	389	222	226	229	1	1	1	
			400	400	400	386	391	386	222	225	228	2	2	2	
			600	600	600	386	390	386	221	225	228	2	2	2	
			800	800	800	385	390	384	221	224	227	3	3	3	
			1000	1000	1000	385	389	384	220	224	227	4	4	4	

Table 5. Measured parameters when using a smartphone

Description	On	Off	Power			Voltage						Current			Information
			R (W)	S (W)	T (W)	RS (V)	ST (V)	TR (V)	RN (V)	TN (V)	SN (V)	R (A)	S (A)	T (A)	
PLN	M10=0	M11=1	0	0	0	0	0	0	0	0	0	0	0	0	Delay 5 seconds after pressing the on/off button
			200	200	200	0	0	0	0	0	0	0	0	0	
	M10=1	M11=10	0	0	0	385	391	386	220	225	229	0	0	0	
			200	200	200	385	391	387	221	225	228	0,8	0,8	0,8	
			400	400	400	384	390	386	220	224	228	1,7	1,6	1,6	
			600	600	600	384	389	385	219	224	228	2,5	2,4	2,4	
Solar power plant	M20=0	M21=1	800	800	800	383	389	384	219	223	227	3,4	3,3	3,3	
			1000	1000	1000	382	388	384	219	223	227	4,2	4,1	4,1	
	M20=1	M21=0	0	0	0	0	0	0	0	0	0	0	0	0	Delay 5 seconds after pressing the on/off button
			200	200	200	0	0	0	0	0	0	0	0	0	
			0	0	0	388	392	388	222	227	229	0	0	0	
			200	200	200	387	392	389	222	226	229	0,8	0,8	0,8	
			400	400	400	386	391	386	222	225	228	1,7	1,6	1,6	
			600	600	600	386	390	386	221	225	228	2,4	2,3	2,3	
			800	800	800	385	390	384	221	224	227	3,2	3,1	3,1	
			1000	1000	1000	385	389	384	220	224	227	4	3,9	3,9	

Table 6. Measured parameters when remotely by IoT

Description	On	Off	Power			Voltage						Current			Information
			R (W)	S (W)	T (W)	RS (V)	ST (V)	TR (V)	RN (V)	TN (V)	SN (V)	R (A)	S (A)	T (A)	
PLN	0	1	0	0	0	0	0	0	0	0	0	0	0	0	Auto switch when the solar power plant goes off
			200	200	200	0	0	0	0	0	0	0	0	0	
	1	0	0	0	0	385	391	386	220	225	229	0	0	0	Delay 10 seconds after the system returns to normal
			200	200	200	385	391	387	221	225	228	0,8	0,8	0,8	
			400	400	400	384	390	386	220	224	228	1,7	1,6	1,6	
			600	600	600	384	389	385	219	224	228	2,5	2,4	2,4	
Solar power plant	0	1	800	800	800	383	389	384	219	223	227	3,4	3,3	3,3	Auto switch when PLN goes out
			1000	1000	1000	382	388	384	219	223	227	4,2	4,1	4,1	
			0	0	0	0	0	0	0	0	0	0	0	0	
			200	200	200	0	0	0	0	0	0	0	0	0	
			0	0	0	385	391	386	220	225	229	0	0	0	
	1	0	200	200	200	385	391	387	221	225	228	0,8	0,8	0,8	
			400	400	400	384	390	386	220	224	228	1,7	1,6	1,6	
			600	600	600	384	389	385	219	224	228	2,5	2,4	2,4	
			800	800	800	383	389	384	219	223	227	3,4	3,3	3,3	
				1000	1000	1000	382	388	384	219	223	227	4,2	4,1	4,1

In scenarios where the solar power plant is inactive, and the PLN system is functioning, power measurements across the phases—designated as R, S, and T—are recorded within a range of 0 to 1,000 W. The inter-phase voltage remains relatively constant, fluctuating between approximately 384 V and 390 V. Similarly, the phase-to-neutral voltage exhibits stability within a range of roughly 218 V to 224 V. Current in each phase shows a proportional increase in relation to the rising power levels, ranging from 0 to 4 A.

In contrast, when the solar power plant is operational, and PLN is not active, the additional power produced by the solar system also gradually increases from 0 to 1,000 W across all phases, reflecting conditions similar to those observed during PLN operation. The voltage measured between phases (R-S, S-T, and T-R) ranges from 388 V to 391 V; this value is slightly elevated compared to that recorded during PLN operations. The phase-to-neutral voltage (R-N, T-N, and S-N) varies from 219 V to 223 V. This rise in voltage within the solar power plant system can be attributed to minimal voltage losses encountered during electrical distribution. Such losses generally result from resistance found in conductors, connections, and equipment. Unlike PLN's extensive distribution network that extends further away from generation sites to end-users, the solar power plant benefits from shorter distribution routes directly connecting its panels. It is important to note that during automated transitions between loads on the solar power plant and PLN or vice versa, these transfers do not occur instantaneously. Instead, a delay of ten seconds is implemented following system stabilization before normal operations can resume.

4. CONCLUSION

A sophisticated control panel for a solar power plant has been successfully designed and manufactured. Testing outcomes demonstrated that this advanced control panel functions efficiently as an ATS control system within an IoT framework. This intelligent control panel facilitates monitoring and operation through smartphones and laptops via the Haiwell cloud application. Assessments were conducted to evaluate both manual and automated measurements of current and voltage, which encompassed on/off pushbutton controls, in addition to manual and automatic readings managed through an HMI. Furthermore, both manual and automated methods were examined with remote control capabilities enabled by the IoT system.

ACKNOWLEDGEMENTS

The authors are grateful to the Center for Research and Community Service, Politeknik Negeri Lhokseumawe, for their assistance and cooperation so that this research can be done well.

FUNDING INFORMATION

The funding agency that has supported the work is the Center for Research and Community Service, Politeknik Negeri Lhokseumawe, through DIPA PNL 2024.

AUTHOR CONTRIBUTIONS STATEMENT

This journal uses the Contributor Roles Taxonomy (CRediT) to recognize individual author contributions, reduce authorship disputes, and facilitate collaboration.

Name of Author	C	M	So	Va	Fo	I	R	D	O	E	Vi	Su	P	Fu
Rudi Syahputra	✓	✓					✓	✓				✓		
Nelly Safitri				✓	✓	✓	✓		✓	✓	✓			
Fauzan		✓				✓		✓	✓	✓	✓	✓		
Yassir	✓	✓		✓			✓			✓	✓		✓	✓
Teuku Hasanuddin	✓	✓		✓			✓			✓	✓		✓	✓
Akhyar					✓	✓								
Radhiah					✓	✓								
Zulfikar					✓	✓								

- C : Conceptualization
- M : Methodology
- So : Software
- Va : Validation
- Fo : Formal analysis
- I : Investigation
- R : Resources
- D : Data Curation
- O : Writing - Original Draft
- E : Writing - Review & Editing
- Vi : Visualization
- Su : Supervision
- P : Project administration
- Fu : Funding acquisition

CONFLICT OF INTEREST STATEMENT

The authors state that no conflict of interest occurred when the research was conducted.

DATA AVAILABILITY

The authors of this article have provided the evidence supporting the available findings in https://drive.google.com/drive/folders/1_i-wA-Np8Xcqo7LL31fbxDhluD0A5Na9?usp=share_link.

REFERENCES

[1] K. Sharma and L. M. Saini, "Power-line communications for smart grid: progress, challenges, opportunities and status," *Renewable and Sustainable Energy Reviews*, vol. 67, pp. 704–751, Jan. 2017, doi: 10.1016/j.rser.2016.09.019.

[2] P. Bunga, M. Pakiding, and S. Silimang, "Design of a remote load control system using smart relay (in *Indoneisan*)," *Jurnal Teknik Elektro dan Komputer*, vol. 4, no. 5, pp. 1–8, 2015, doi: 10.35793/jtek.v4i5.9989.

[3] M. I. Nur and M. Aryanto, "Development of a stirring robot prototype in the grain drying process using internet of things-based solar power," Thesis, Dept. Elect. Eng., Ujung Pandang State Polytechnic, Makassar, Indonesia, 2020.

[4] M. Ozcan, "Factors influencing the electricity generation preferences of Turkish citizens: Citizens' attitudes and policy recommendations in the context of climate change and environmental impact," *Renewable Energy*, vol. 132, pp. 381–393, Mar. 2019, doi: 10.1016/j.renene.2018.08.006.

[5] R. R. A. Siregar and N. Wardana, "Electrical panel performance monitoring system (in *Indonesia*)," *JETri*, vol. 14, no. 2, pp. 81–100, Feb. 2017.

[6] M. Junus, S. Wirayoga, and Adzikirani, "System design renewable energy using applications bright energy solar meter panel based on the internet of things," 2023, pp. 89–101. doi: 10.2991/978-94-6463-358-0_10.

[7] M. F. Pratama, "Solar power monitoring and control system using fuzzy logic-based IoT (in *Indonesian*)," Thesis, Magister Teknik Elektro, Universitas Islam Sultan Agung, Semarang, Indonesia, 2021.

[8] T. Darmanto and H. Krisma, "Implementation of IoT technology for controlling android-based household electronic equipment," *Jurnal Teknologi Informasi Universitas Muhammadiyah Pontianak (STIUST)*, 2019.

[9] L. Wibowo, R. Wahyusari, T. Yuwono, and A. Shofia, "IoT-based high-accuracy monitoring system for on-grid photovoltaic power system using NodeMCU ESP8266 and PZEM004T," *Journal of Mechatronics, Electrical Power, and Vehicular Technology*, vol. 15, no. 2, pp. 230–241, Dec. 2024, doi: 10.55981/j.mev.2024.823.

[10] F. A. Silaban, E. N. W. Putra, and L. M. Silalahi, "Monitoring and evaluation electrical power control in solar power systems based on IoT," *CCIT Journal*, vol. 17, no. 2, pp. 170–183, May 2024, doi: 10.33050/ccit.v17i2.2996.

[11] J. M. Ramadhan, R. Mardiaty, and I. N. Haq, "IoT monitoring system for solar power plant based on MQTT publisher / subscriber protocol," in *Proc. 7th International Conference on Wireless and Telematics (ICWT)*, 2021, pp. 1–6, doi: 10.1109/ICWT52862.2021.9678371.

[12] M. O. Onibonjo, O. O. Alegbeleye, and A. O. Ojo, "Control design and management of a distributed energy resources system," *International Journal of Technology*, vol. 14, no. 2, pp. 236–245, Apr. 2023, doi: 10.14716/ijtech.v14i2.5884.

[13] R. A. Asmara et al., "Proceedings of the 5th Annual Advanced Technology, Applied Science, and Engineering Conference (ATASEC) 2023," in *Advances in Engineering Research* 229, 2024. [Online]. Available: <https://books.google.co.id/books?id=FrXtEAAAQBAJ>.

[14] K. Krismadinata, P. Kusuma, and Y. Yahfizham, "Design and manufacture of wireless monitoring system of photovoltaic generation employing Raspberry PI 3," *Elkha*, vol. 13, no. 1, p. 19, 2021, doi: 10.26418/elkha.v13i1.42888.

[15] N. Iksan, P. Purwanto, and H. Sutanto, "Real-time monitoring of photovoltaic systems and control of electricity supply for smart micro grid-PV using IoT," *TEM Journal*, vol. 13, no. 1, pp. 514–523, Feb. 2024, doi: 10.18421/TEM131-53.

[16] B. Aryanto, B. W. Sanjaya, H. Sujaini, S. D. Panjaitan, R. R. Yacoub, and N. Miharja, "Application of photovoltaic panels as producers of electrical energy with iot technology based on programmable logic controller," *Elkha*, vol. 16, no. 1, p. 21, 2024, doi: 10.26418/elkha.v16i1.76663.

- [17] Politeknik Negeri Lhokseumawe, "MoA between CV," *Cotindo Jaya and Department of Electrical Engineering*.
- [18] OMRON, "NB-designer operation manual," OMRON. [Online]. Available: https://files.omron.eu/downloads/latest/manual/en/v106_nb-designer_software_operation_manual_en.pdf?v=1
- [19] Xiamen Haiwell Technology Co., Ltd., "User's manual of haiwell cloud APP," 2020. [Online]. Available: <https://haiwell.com/daruanjianen/User%27s%20Manual%20of%20Haiwell%20Cloud%20APP.pdf>.
- [20] Xiamen Haiwell Technology Co., Ltd., "User's manual of haiwell card-type PLC MPU," 2020. [Online]. Available: <https://www.haiwell.com/daruanjianen/User%27s%20Manual%20of%20Haiwell%20Card-type%20PLC%20MPU.pdf>.
- [21] Xiamen Haiwell Technology Co., Ltd., "User's manual of haiwell IoT cloud HMI," 2020. [Online]. Available: <https://haiwell.com/daruanjianen/User%27s%20Manual%20of%20Haiwell%20IoT%20Cloud%20HMI.pdf>.
- [22] Blynk, "Blynk - IEEE internet of things," IEEE IoT Startup Profile, Dec. 2015. [Online]. Available: https://iot.ieee.org/images/files/pdf/startups/2015-12_startup_night-blynk.pdf
- [23] D. Apdilah, "IoT-based smart waste system using blynk application," *InfoTekJar (Jurnal Nasional Informatika dan Teknologi Jaringan)*, vol. 8, no. 2, pp. 47–52, 2024, doi: 10.30743/infotekjar.v8i2.9905.
- [24] A. Filipescu, G. Simion, D. Ionescu, and A. Filipescu, "IoT-cloud, VPN, and digital twin-based remote monitoring and control of a multifunctional robotic cell in the context of AI, Industry, and Education 4.0 and 5.0," *Sensors*, vol. 24, no. 23, p. 7451, Nov. 2024, doi: 10.3390/s24237451.
- [25] Hairul, F. Arifin, R. Wilza, Z. Zakaria, Kurniawan, and Y. D. Herlambang, "Automation of load electricity operating system using PLC (programmable logic controller)," *International Journal of Research in Vocational Studies (IJRVOCAS)*, vol. 3, no. 1, pp. 76–81, May 2023, doi: 10.53893/ijrvocas.v3i1.200.

BIOGRAPHIES OF AUTHORS



Rudi Syahputra, S.T., M.Eng.    received his bachelor's degree in Electrical Engineering from Universitas Brawijaya, East Java, in 2002. He then completed his postgraduate studies at Gajah Mada University, Yogyakarta, in 2011, in Electrical Engineering with a concentration in Power Generation. Since 2006, he has been serving as a lecturer in the Department of Electrical Engineering at Politeknik Negeri Lhokseumawe. He can be contacted at email: rudisyahputra@pnl.ac.id.



Dr. Nelly Safitri, S.S.T., M.Eng.Sc.    born in Lhokseumawe, Aceh, Indonesia on 21 January 1978. Currently works as lecturer and researcher at Electrical Engineering Department, Politeknik Negeri Lhokseumawe. Successfully completed her Master and Doctoral degree at Curtin University of Technology, Western Australia in Electrical and Computer Engineering Department in 2007 and 2016, respectively. Her area of interests is renewable energy, power system, and smartgrid. She can be contacted at email: nellysafitri@pnl.ac.id.



Fauzan, S.T.M.Eng.    born in Bireuen, Bireuen Regency on April 12, 1974. He obtained his Bachelor's degree at the University of Iskandar Muda, Department of Electrical Engineering in 1998. Continued his postgraduate studies at Gajah Mada University (2009-2012) in Electrical Engineering, concentrating on Electrical Power Engineering. Then he became a lecturer at Department of Electrical Engineering, Politeknik Negeri Lhokseumawe, from 2003 until now. He has served as Head of the energy generation engineering technology study program in 2024 until now. He can be contacted at email: fauzan@pnl.ac.id.




Yassir, ST., M.Eng.    born in Aceh Besar, January 6, 1973. The author earned a Bachelor of Engineering degree in Electrical Engineering from the University of North Sumatra in 2000. Subsequently, in 2013, he earned a Master of Engineering (M.Eng.) degree in the same field from Gadjah Mada University. Currently, the author is the Head of the Electrical Engineering Department of Politeknik Negeri Lhokseumawe. The author is also a competency assessor from BNSP. The author actively publishes scientific works, including in international journals, national journals, and in proceedings of international and national scientific meetings in the field of power plant optimization and renewable energy. He can be contacted at email: yassir@pnl.ac.id.



Teuku Hasanuddin, S.T.M.Eng.    born in Sigli, Pidie Regency on October 10, 1974. He obtained his Bachelor's degree at the University of North Sumatra, Department of Electrical Engineering in 1999. Continued his postgraduate studies at Gajah Mada University (2007-2009) in Electrical Engineering, concentrating on Electrical Power Engineering. Then he became a lecturer at the Lhokseumawe State Polytechnic, Department of Electrical Engineering from 2002 until now. Currently he is a Secretary of the Electrical Engineering Department, Politeknik Negeri Lhokseumawe. He is also an expert staff for external and internal lightning distribution system assessment in the pema global energi project in 2024. He can be contacted at email: teukuhasanuddin@pnl.ac.id.



Akhyar, S.T., M.T.    born in Lheu, Aceh Besar Regency, on May 3, 1966, obtained a Bachelor of Engineering in Electrical Engineering from Medan Area University in 1995. Then completed his postgraduate studies at Brawijaya University Malang, East Java in 2010 in Mechanical Engineering with a concentration in Industrial Management. Currently he is a lecturer at the Department of Electrical Engineering, Politeknik Negeri Lhokseumawe. His research areas include industrial electronics, solar power generation, renewable energy, and power electronics. He can be contacted at email: akhyar.pnl@pnl.ac.id.



Radhiah, S.T., M.T.    currently works as lecturer and researcher at Electrical Engineering Department, Politeknik Negeri Lhokseumawe. Successfully completed her Master degree at University of North Sumatera in Indonesia in 2008. Her area of interests is power system, power electronics and electrical machinery. She can be contacted at email: radhiah@pnl.ac.id.



Zulfikar, ST. MT.    born in Geumpang, Pidie Regency, on December 31, 1970. obtained a bachelor of Engineering in Electrical Engineering from Iskandar Muda University in 1997. Subsequently, he continued his postgraduate studies at Gadjah Mada University in 2007. and obtained a Master of Engineering in Electrical Engineering with a concentration in Electrical Power Engineering. Since 1999, he has worked as a lecturer at the Department of Electrical Engineering, Politeknik Negeri Lhokseumawe. Currently he is the Head of the Electrical Engineering Department Laboratory. His research areas include solar power generation, wind power generation, and fuel cell. He can be contacted at email: zul_elka@pnl.ac.id.